

BACKHOES



Model KB2465

* Specifications may vary depending on tractor model and are subject to change without notification. Tractors must be equipped with ROPS and seat belt that will provide greater safety.

STANDARD FEATURE

- Sub-frame mounted.
- Factory assembled.
- Responsive two-lever hydraulic control with exceptional feathering characteristics.
- Anti-drop load-checks.
- Standard buckets, 9", 12", 16", 18", 24" and 36" wide ditch and grave buckets.
- All buckets have replaceable teeth.
- Extra heavy duty buckets.

SPECIFICATIONS

MODEL	KB2465
▶ Digging Depth	76.3"
▶ Reach (From center of Swing Pivot)	113.1"
▶ Loading Height (Bucket at 60 ^o /Æ)	63.6"
▶ Swing Arc	180°
▶ Transport Height (Maximum)	77.2"
▶ Transport Overhang	43.5"
▶ Bucket Rotation	180°
▶ Stabilizer Spread (Down Position)	68.7"
▶ Stabilizer Spread (Up Position)	46.4"
▶ Shipping Weight (Less Bucket)	1,036 lbs
▶ Bucket Digging Force	2,817.5 lbs
▶ Dipper-stick Digging Force	1,748 lbs
▶ Operating Pressure	2,466 psi

APPLICATION CHART

Backhoe	DS Series		CK Series				DK Series					LK Series
	4110	4510	20S	27	30	35	35SE	40SE	45SE	50SE	55	30 (TLB)
KB2465			X									
KB2475				X	X	X						X
KB2485	X	X					X	X	X	X	X	