

BACKHOES



Model KB2485

* Specifications may vary depending on tractor model and are subject to change without notification. Tractors must be equipped with ROPS and seat belt that will provide greater safety.

STANDARD FEATURE

- Sub-frame mounted.
- Factory assembled.
- Responsive two-lever hydraulic control with exceptional feathering characteristics.
- Anti-drop load-checks.
- Standard buckets, 9", 12", 16", 18", 24" and 36" wide ditch and grave buckets.
- All buckets have replaceable teeth.
- Extra heavy duty buckets.

SPECIFICATIONS

MODEL	KB2485
▶ Digging Depth	94.4"
▶ Reach (From center of Swing Pivot)	136.1"
▶ Loading Height (Bucket at 60°/E)	80.3"
▶ Swing Arc	180°
▶ Transport Height (Maximum)	92.9"
▶ Transport Overhang	50.4"
▶ Bucket Rotation	180°
▶ Stabilizer Spread (Down Position)	68.7"
▶ Stabilizer Spread (Up Position)	46.4"
▶ Shipping Weight (Less Bucket)	1,102 lbs
▶ Bucket Digging Force	3,748 lbs
▶ Dipper-stick Digging Force	2,205 lbs
▶ Operating Pressure	2,466 psi

APPLICATION CHART

Backhoe	DS Series		CK Series				DK Series					LK Series
	4110	4510	20S	27	30	35	35SE	40SE	45SE	50SE	55	30 (TLB)
KB2465			X									
KB2475				X	X	X						X
KB2485	X	X					X	X	X	X	X	