

Manufacturer Model Drive Type	KIOTI CK27 HST 4WD	Bobcat CT225 4WD	Challenger MT255B HST 4WD	John Deere 2520 4WD	Kubota B2630 HSD	Mahindra 2615 HST	Mahindra 2815 HST	Massey Ferg 1528 HST 4WD	McCormick CT28HST 4WD	Montana T2734 4WD	Montana R2844 HST	New Holland T1110 FWD
Engine												
Type	3 Cyl. Diesel	3 Cyl. Diesel	3 Cyl. Diesel	3 Cyl. Diesel	3 Cyl. Diesel	3 Cyl. Diesel	3 Cyl. Diesel	3 Cyl. Diesel	4 Cyl. Diesel	3 Cyl. Diesel	4 Cyl. Diesel	3 Cyl. Diesel
Gross HP	28	27	28.4	26.5	26	26	28	28.4	28	27	28	28
PTO HP	20.5	19.5	22.3	20.5	19.5	23	23	22.3	22	20.7	22	20.5
Displacement Cu.In.	85	85.4	89.3	81.2	98.5	80.4	91.3	89.3	91.5	80.4	91.5	69
Fuel Capacity Gal.	7.9	7.9	7.9	7.1	8.1	NP	NP	7.9	8.5	6.6	8.45	7.1
Drive Train												
Clutch	Dry single	NP	NP	N/A	N/A	Dry Single	Dry Single	NP	NP	Wet Multi Disc	NP	NP
Transmission	Hydrostatic	Hydrostatic	Hydrostatic	Hydrostatic	Hydrostatic	Hydrostatic	Hydrostatic	Hydrostatic	Hydrostatic	Hydrostatic	Hydrostatic	Hydrostatic
Speeds	Inf. 3	Inf. 3	Inf. 3	Inf. 2	Inf. 3	Inf. 3	Inf. 3	Inf. 3	Inf. 3	Inf. 2	Inf. 3	Inf. 2
Differential Lock	STD	STD	STD	STD	STD	NP	NP	STD	STD	NP	STD	STD
Brake Type	Wet Disc	Wet Disc	Wet Multi Disc	Wet Disc	Wet Multi Disc	Wet Disc	Wet Disc	Wet Disc	Wet Disc	Wet Disc	Wet Multi Disc	Wet Disc
PTO Type	Live	Live	Independent	Independent	Independent	Live	Live	Live-Indep.	Independent	Independent	Independent	Independent
Rear (RPM)	540 (1000 OPT)	540	540	540	540	540	540	540	540	540	540	540
Mid (RPM)	2000 OPT	2000 OPT	2000	2100	2542	2000	2000	2000	OPT	2000	OPT	2200
Hydraulic System												
Pump	Gear Tandem	NP	Open Center	Gear	Dual Pump	Open Center	Open Center	Open Center	Dual Pump	Single Pump	NP	Gear
Total Hydraulic Flow (gpm)	12.7	12.7	10	10.5	9.8	7.8 valve flow	7.4	10	11.6	7.6	11.3	13
3-Point Hitch	Cat. 1	Cat. 1	Cat. 1	Cat. 1	Cat. 1	Cat. 1	Cat. 1	Cat. 1	Cat. 1	Cat. 1	Cat. 1	Cat. 1
Lift Capacity at 24" behind lift point Lbs.	1,764	1,400	1,610	1,150	1,676	2,205*	2,646*	2,425 at hitch point	2,620 at ball end	1,102	2,619 at ball end	1,000
Steering	Hydro. Power	Hydro. Power	Hydro. Power	Power	Hydro. Power	Hydro. Power	Hydro. Power	Hydro. Power	Hydro. Power	Hydro. Power	Hydro. Power	Hydro. Power
Dimensions												
Overall Length IN.	122.2	122.2	112.4	NP	99.2	115	121.3	112.4	117.6	113.4	117	98.5
Overall Width IN.	54.6	55.4	55.1	NP	53.8	59.4	59.8	53.5	NP	52.8	NP	52
Overall Height IN.	96.8	95.9	80.7	NP	NP	NP	NP	80.7	91.1	94.4	91	76
Wheel Base IN.	66.1	66.1	65.6	65.2	65.5	NP	NP	65.6	65.4	58.3	65	57.5
Turning Radius FT.	9.5	9.5	9.1	7.5	6.9	7.9	7.8	NP	8.4	NP	8.4	6.8
Weight with ROPS Lbs.	3,117*	3,021*	2,423*	1,865*	1,786	2,458**	2,555**	2,423*	2,646	1,984*	2,645	1,492*
Warranty												
Warranty	4 year (2 Year Bumper to Bumper and 2 year Engine and Drive line)	NP	NP	24 Month or 2000Hr (whichever comes first), Powertrain 36 Month or 2000Hr (whichever comes first)	24 Month or 2000Hr (whichever comes first), Powertrain 36 Month or 2000Hr (whichever comes first)	3 Year Engine and Powertrain Warranty	3 Year Engine and Powertrain Warranty	2 year/ 2000 Hr All inclusive (whichever is first), 3 year/ 2000Hr engine/ Powertrain (whichever is first)	NP	NP	NP	Full 24 month, additional 12 month Powertrain
Notes												
Notes	*wt. with Ag Tires	*wt. with Ag Tires	* field ready, Industrial Tires NOTE-Their website no longer lists the MT200B series	*Shipping weight		*Lift specs did not say where measured from **Operating weight	*Lift specs did not say where measured from **Operating weight	*Shipping weight		*weight with standard tires		*Shipping weight with Ag tires

N/A - Not Available

NP - Not Published

OPT - Optional

Manufacturer Model Drive Type	KIOTI CK27 HST 4WD	TYM T273HST 4WD
Engine		
Type	3 Cyl. Diesel	3 Cyl. Diesel
Gross HP	28	27
PTO HP	20.5	23
Displacement Cu.In.	85	80.4
Fuel Capacity Gal.	7.9	6.6
Drive Train		
Clutch	Dry single	N/A
Transmission	Hydrostatic	Hydrostatic
Speeds	Inf. 3	Inf. 2
Differential Lock	STD	NP
Brake Type	Wet Disc	Wet Disc
PTO Type	Live	Independent
Rear (RPM)	540 (1000 OPT)	540
Mid (RPM)	2000 OPT	2000
Hydraulic System		
Pump	Gear Tandem	Single Pump
Total Hydraulic Flow (gpm)	12.7	7.6
3-Point Hitch	Cat. 1	Cat. 1
Lift Capacity at 24" behind lift point Lbs.	1,764	1,102
Steering	Hydro. Power	Hydro. Power
Dimensions		
Overall Length IN.	122.2	94.5
Overall Width IN.	54.6	49
Overall Height IN.	96.8	79.5
Wheel Base IN.	66.1	58.3
Turning Radius FT.	9.5	NP
Weight with ROPS Lbs.	3,117*	2,028*
Warranty		
Warranty	4 year (2 Year Bumper to Bumper and 2 year Engine and Drive line)	5 Year (3 Year bumper to Bumper; 4th year Parts & Labor - Drivetrain; 5th year Drivetrain Parts only)
Notes		
Notes	*wt. with Ag Tires	*weight with standard tires

N/A - Not Available