

Manufacturer Model Drive Type	KIOTI CK35 4WD	Branson 3510 i 4WD	Challenger MT265B 4WD	John Deere 3320 4WD	Kubota L3240 DT 4WD	Mahindra 3510 4WD	Massey Ferg 1533 4WD	Montana 3240 4WD	Montana R3644	New Holland T1520 4WD	TYM T330 4WD	YTO 354 4WD
Engine												
Type	3 Cyl. Diesel	3 Cyl. Diesel	3 Cyl. Diesel	3 Cyl. Diesel	3 Cyl. Diesel	3 Cyl. Diesel	3 Cyl. Diesel	3 Cyl. Diesel	4 Cyl. Diesel	3 Cyl. Diesel	3 Cyl. Diesel	3 Cyl. Diesel
Gross HP	34	35	33	32.5	34	34	33	32	38.5	35	33.5	36.9
PTO HP	27.6	30	26	25.5	26.5	28.7	26	NP	31	29.5	26.5	NP
Displacement Cu.In.	100.5	104.6	91.4	100.2	100.5	100.3	91.4	103.74	107.3	101.4	91.4	NP
Fuel Capacity Gal.	7.9	11	10.6	13.5*	11.6	NP	10.6	7.4	8.5	7.1	8.7	NP
Drive Train												
Clutch	Dry Dual	Dry Single	Wet multi Disc	Wet multi Disc	Dry Single	Dry Single	NP	NP	NP	Dry	Dry Single	Double Action
Transmission	Syn. Shuttle	Syn. Shuttle	Syn. Shuttle	Power Reverser	Fully Syn GST	Syn. Shuttle	Syn. Shuttle	Syn. Shuttle	Syn. Shuttle	Mechanical	Syn. Shuttle	Gear
Speeds	8F8R	12F12R	8F8R	12F12R	8F8R	12F12R	8F8R	8F8R	12F12R	9F3R	12F12R	NP
Differential Lock	STD	STD	STD	STD	NP	STD	NP	STD	STD	STD	NP	NP
Brake Type	Wet Disc	Wet Disc	Wet Multi Disc	Wet Disc	Wet Disc	Wet Disc	Wet Disc	Wet Multi Disc	Wet Multi-disc	Wet Disc	Wet Disc	Wet Disc
PTO Type	Live	Independent	Independent	Independent	Independent	Live	Independent	Independent	Independent	Live	Independent	Live
Rear (RPM)	540 (1000 OPT)	540/100	540	540	540	540/1000	540	540	540	540	540	540/1000
Mid (RPM)	2000 OPT	N/A	2000 OPT	2100 OPT	2000 OPT	N/A	2000 OPT	NP	OPT	N/A	2000	NP
Hydraulic System												
Pump	Gear Tandem	Open Center	Open Center	Dual Gear	NP	Open Center	Gear	NP	NP	Gear	Dual Gear	NP
Total Hydraulic Flow (gpm)	12.7	13.2	12.7	13.9	13.2	7.9 valve flow only rated	14	5.8 valve flow only rated	11.7	10	9.7	NP
3-Point Hitch	Cat. 1	Cat. 1	Cat. 1	Cat. 1	Cat. 1	Cat. 1	Cat. 1	Cat. 1	Cat. 1	Cat. 1	Cat. 1	NP
Lift Capacity at 24" behind lift point Lbs.	1,764	2,140 at lift point	2,535	2,220	2,646	2,865*	2,800 at hitch point	1,596 at ball end	2,619 at ball end	1,635	1,199	1,709
Steering	Hydro. Power	Hydro. Power	Hydro. Power	Power	Hydro. Power	Hydro. Power	Hydro. Power	Hydro. Power	Hydro. Power	Hydro. Power	Hydro. Power	NP
Dimensions												
Overall Length IN.	122.2	119	121	120.2	114.8	127	121	115.4	117	111.4	129	135.8
Overall Width IN.	54.6	57	62.2	68.4	59.8	66.9	62	52.2	41.7	62	52	65.9
Overall Height IN.	96.8	95	87.4	93.3	90.7	NP	87.4	94.1	91	83.5	92	59.8
Wheel Base IN.	66.1	65	69.7	68	71.1	NP	70	NP	65	63	64	70
Turning Radius FT.	9.5	7.9	9.2	8.8	8.9	8.2	8.1	9.6	8.4	8.7	7.75	13.2
Weight with ROPS Lbs.	3,151	3,756	3,136	2,900*	3,252*	3,483**	3,025*	2,659*	2,712	2,400*	3,064	3,880*
Warranty												
Warranty	4 year (2 Year Bumper to Bumper and 2 year Engine and Drive line)	4 year limited	NP	24 Month or 2000Hr (whichever comes first), Powertrain 36 Month or 2000Hr (whichever comes first)	24 Month or 2000Hr (whichever comes first), Powertrain 36 Month or 2000Hr (whichever comes first)	NP	2 year/ 2000 Hr All inclusive (whichever is first), 3 year/ 2000Hr engine/ Powertrain (whichever is first)	NP	NP	Full 24 month, additional 12 month Powertrain	5 Year (3 Year bumper to Bumper; 4th year Parts & Labor - Drivetrain; 5th year Drivetrain Parts only)	NP
Notes												
Notes	*wt. with Ag Tires		* field ready, Industrial Tires NOTE-Their website no longer lists the MT200B series	*Shipping weight	*Wt with cab 3748 lbs. OPT Transmission GST 12F8R or Hydrostatic	*Lift specs did not say where measured from **Operating weight	*Shipping weight	*Wt without ROPS		*Shipping weight with Ag tires		*ROPS is optional

N/A - Not Available

NP - Not Published

OPT - Optional