

| Manufacturer Model Drive Type               | KIOTI DK35SE 4WD  | Branson 3820 i 4WD  | Deutz-Fahr Agrokid 210 4WD | John Deere 3520 4WD   | Kubota L3540 GST 4WD  | Mahindra 3510 4WD   | Massey Ferg 2605 4WD | McCormick CT36 4WD | Montana 3840 4WD  | New Holland T1520 4WD                         | TYM T353 4WD  |
|---|---|---------------------|----------------------------|---|---|---|----------------------|--------------------|-------------------|---|---|
| <b>Engine</b>                               |   |                     |                            |   |   |   |                      |                    |                   |   |   |
| Type  | 3 Cyl. Diesel   | 4 Cyl. Diesel       | 4 Cyl. Diesel              | 4 Cyl. Diesel   | 3 Cyl. Diesel   | 3 Cyl. Diesel   | 3 Cyl. Diesel        | 4 Cyl. Diesel      | 4 Cyl. Diesel     | 3 Cyl. Diesel                                 | 4 Cyl. Diesel   |
| Gross HP                                    | 38  | 38                  | 39                         | 37  | 37  | 34  | 38.5                 | 38.5               | 38                | 35  | 35  |
| PTO HP                                      | 28.5  | 32                  |                            | 30.5  | 29.5  | 28.7  | 30                   | 31                 | NP                | 29.5  | 29  |
| Displacement Cu.In.                         | 111.43  | 127.2               | 91.5                       | 91.5  | 111.4   | 100.3   | 152.6                | 107.3              | 109.8             | 101.4   | 107.3   |
| Fuel Capacity Gal.                          | 11.9  | 11                  | 10                         | 13.5*   | 11.6  | NP  | 11.1                 | 8.5                | 10.6              | 7.1   | 9   |
| <b>Drive Train</b>                          |   |                     |                            |   |   |   |                      |                    |                   |   |   |
| Clutch                                      | Dry Single  | Dry Single          | NP                         | Wet   | Dry Single  | Dry Single  | Dry Single           | NP                 | NP                | Dry   | Dry Single  |
| Transmission                                | Syn. Shuttle  | Syn. Shuttle        | Syn. Shuttle               | Power Reverser  | GST   | Syn. Shuttle  | Center Shift         | Syn. Shuttle       | Syn. Shuttle      | Mechanical                                    | Syn. Shuttle  |
| Speeds                                      | 12F12R  | 12F12R              | 12F12R                     | 12F12R  | 12F8R   | 12F12R  | 8F2R                 | 12F12R             | 12F12R            | 9F3R  | 12F12R  |
| Differential Lock                           | STD   | STD                 | STD                        | STD   | NP  | STD   | STD                  | STD                | STD               | STD   | NP  |
| Brake Type                                  | Wet Disc  | Wet Disc            | Wet Disc                   | Wet Disc  | Wet Disc  | Wet Disc  | Dry Drum             | Wet Disc           | Wet Multi Disc    | Wet Disc                                      | Wet Disc  |
| PTO Type                                    | Hydro. Indep.   | Independent         | Independent                | Independent   | Independent   | Live  | Independent          | Independent        | Independent       | Live  | Independent   |
| Rear (RPM)                                  | 540   | 540/1000            | 540                        | 540   | 540   | 540/1000  | 540                  | 540                | 540               | 540   | 540/1000  |
| Mid (RPM)                                   | 2000 OPT  | N/A                 | 2000                       | 2100 OPT  | 2000 OPT  | NP  | N/A                  | OPT                | NP                | N/A   | N/A   |
| <b>Hydraulic System</b>                     |   |                     |                            |   |   |   |                      |                    |                   |   |   |
| Pump  | Gear Tandem   | Open Center         | NP                         | Dual Gear   | NP  | Open Center   | Gear                 | NP                 | NP                | Gear  | Dual Gear   |
| Total Hydraulic Flow (gpm)                  | 15.2  | 13.2                | 11.9                       | 13.9  | 13.2  | 7.9 valve flow only rated   | 20.9                 | 11.6               | 8.1               | 10  | 10.6  |
| 3-Point Hitch                               | Cat. 1  | Cat. 1              | Cat. 1                     | Cat. 1  | Cat. 1  | Cat. 1  | Cat. 1 & 2           | Cat. 1             | Cat. 1            | Cat. 1  | Cat. 1  |
| Lift Capacity at 24" behind lift point Lbs. | 2,383   | 2,580 at lift point | 2,640 at lift point        | 2,200   | 2,646   | 2,865*  | 3,195 at hitch point | 2,620 at ball end  | 2,977 at ball end | 1,635   | 1,764   |
| Steering                                    | Hydro. Power  | Hydro. Power        | Hydro. Power               | Power   | Hydro. Power  | Hydro. Power  | Hydro. Power         | Hydro. Power       | Hydro. Power      | Hydro. Power                                  | Hydro. Power  |
| <b>Dimensions</b>                           |   |                     |                            |   |   |   |                      |                    |                   |   |   |
| Overall Length IN.                          | 129.1   | 124                 | 116                        | NP  | NP  | 127   | 130                  | 117.6              | 130.3             | 111.4   | 126   |
| Overall Width IN.                           | 61.6  | 72                  | 53.5                       | NP  | 59.8  | 66.9  | 66                   | NP                 | 66                | 62  | 53.5  |
| Overall Height IN.                          | 93.1  | 97                  | 77                         | NP  | 90.7  | NP  | 92                   | 91.1               | 87.5              | 83.5  | 94.5  |
| Wheel Base IN.                              | 69.5  | 69                  | 69                         | 68  | 71.1  | NP  | 77                   | 65.4               | 63                | 63  | 64.5  |
| Turning Radius FT.                          | 9.3   | 8.4                 | 8.5                        | 8.8   | 8.9   | 8.2   | NP                   | 8.4                | 9.5               | 8.7   | 7.75  |
| Weight with ROPS Lbs.                       | 3,963*  | 4,087               | 2,750*                     | 2,900*  | 3,296*  | 3,483**   | 4,530*               | 2,711              | 3,418*            | 2,400*  | 3,065   |
| <b>Warranty</b>                             |   |                     |                            |   |   |   |                      |                    |                   |   |   |
| Warranty                                    | 4 year (2 Year Bumper to Bumper and 2 year Engine and Drive line) | 4 year limited      | NP                         | 24 Month or 2000Hr (whichever comes first), Powertrain 36 Month or 2000Hr (whichever comes first) | 24 Month or 2000Hr (whichever comes first), Powertrain 36 Month or 2000Hr (whichever comes first) | 3 Year Engine and Powertrain Warranty                             | NP                   | NP                 | NP                | Full 24 month, additional 12 month Powertrain | 5 Year (3 Year bumper to Bumper; 4th year Parts & Labor - Drivetrain; 5th year Drivetrain Parts only) |
| <b>Notes</b>                                |   |                     |                            |   |   |   |                      |                    |                   |   |   |
| Notes                                       | *wt. with Ag Tires  |                     | *wt. with Ag Tires         | *Shipping weight  | *Wt with cab 3748 lbs.  | *Lift specs did not say where measured from<br>**Operating weight | *Operating weight    |                    | *Wt without ROPS  |   |   |

N/A - Not Available

NP - Not Published

OPT - Optional