

Manufacturer Model Drive Type	KIOTI DK40SE 4WD	Branson 4220i 4WD	Case Farmall 40 MFD	Challenger MT275B 4WD	John Deere 4120 4WD	Kubota L3940GST 4WD	Mahindra 4110 4WD	Massey Ferg 1540 SS 4WD	McCormick CT41 4WD	Montana 3940 4WD	Montana R4344	New Holland T2310 G FWD	Shire 440 4WD
<b>Engine</b>													
Type	4 Cyl. Diesel	4 Cyl. Diesel	4 Cyl. Diesel	4 Cyl. Diesel	4 Cyl. Diesel	4 Cyl. Diesel	4 Cyl. Diesel	3 Cyl. Diesel	4 Cyl. Diesel	4 Cyl. Diesel	4 Cyl. Diesel	4 Cyl. Diesel	4 Cyl. Diesel
Gross HP	41	42	40	40.1	43.1	40.5	40.4	40.1	41	39	41	40	40
PTO HP	34	36	35	31	37	33	33.6	31	36	NP	36	35	NP
Displacement Cu.In.	121.98	127.2	121.7	91.4	148.9	122	122	91.4	141.0	109.84	141	121.7	NP
Fuel Capacity Gal.	11.9	11	13	10.6	14.5	13.2	NP	10.6	10	10.6	10	13	NP
<b>Drive Train</b>													
Clutch	Dry Single	Dry Single	Dry Disk	Wet Multi Disc	Wet Multi Disc	Dry Single	Dry Single	Wet Multi Disc	NP	NP	NP	Wet Disc	NP
Transmission	Syn. Shuttle	Syn. Shuttle	Syn. Shuttle	Syn. Shuttle	Power Rev.	GST	Syn. Shuttle	Syn. Shuttle	Syn Shuttle	Syn. Shuttle	Syn Shuttle	Syn. Shuttle	NP
Speeds	12F12R	12F12R	12F12R	8F8R	12F12R	12F8R	12F12R	8F8R	16F16R	12F12R	16F16R	12F12R	8F2R
Differential Lock	STD	STD	NP	STD	STD	NP	STD	STD	STD	STD	NP	STD	STD
Brake Type	Wet Disc	Wet Disc	Wet Disc	Wet multi Disc	Wet Disc	Wet Disc	Wet Disc	Wet multi Disc	Wet Disc	Wet Multi Disc	Wet multi Disc	Wet Disc	NP
PTO Type	Hydro. Indep.	Independent	Independent	Independent	Independent	Independent	Independent	Independent	Independent	Independent	Ground (Indep OPT)	Independent	NP
Rear (RPM)	540	540/1000	540	540	540	540	540/1000	540	540	540	540	540	540/1000
Mid (RPM)	2000 OPT	N/A	N/A	2000 OPT	2100 OPT	2000 OPT	NP	2000 OPT	OPT	NP	OPT	N/A	NP
<b>Hydraulic System</b>													
Pump	Gear Tandem	Open Center	Gear	Open Center	Dual Gear	NP	Open Center	Dual Gear	NP	NP	NP	Gear	NP
Total Hydraulic Flow (gpm)	16.8	13.2	14.9	12.7	17.1	14.7	9.5 valve flow	14	12.3	8.2	12.3	14.9	NP
3-Point Hitch	Cat. 1	Cat. 1	Cat. 1	Cat. 1	Cat. 1	Cat. 1	Cat. 1	Cat. 1	Cat. 1	Cat. 1	Cat. 1	Cat. 1	Cat.1
Lift Capacity at 24" behind lift point Lbs.	2,493	2,580 at lift point	2,330	2,535	2,500	2,756	2,865*	2,800 at hitch point	2,756 at ball end	2,695 at ball end	2,755 at ball end	2,330	NP
Steering	Hydro. Power	Hydro. Power	Hydro. Power	Hydro. Power	Hydro. Power	Hydro. Power	Hydro. Power	Hydro. Power	Hydro. Power	Hydro. Power	Hydro. Power	Hydro. Power	Power
<b>Dimensions</b>													
Overall Length IN.	134.2	124	125.5	121	128.2	121.5	139	121	125.7	132	125	125.2	135.4
Overall Width IN.	63.9	72	66.6	62.2	90	66.5	71.2	62	NP	66	43.3	66.6	59
Overall Height IN.	95	97	95	87.4	97.2	97.4	NP	87.4	95.1	87.5	95	95	92.9
Wheel Base IN.	74	69	73.5	69.7	71.5	74.6	NP	70	69.2	66.2	69	73.5	NP
Turning Radius FT.	9.5	8.4	NP	9.2	9.2	8.1	10.2	NP	8.4	10.7	8.3	9.2	NP
Weight with ROPS Lbs.	4,202*	4,105	3,433	3,169*	3,700*	3,527*	3,969**	3,058*	3,583	2,955*	3,582	3,295*	NP
<b>Warranty</b>													
Warranty	4 year (2 Year Bumper to Bumper and 2 year Engine and Drive line)	4 year limited	NP	NP	24 Month or 2000Hr (whichever comes first), Powertrain 36 Month or 2000Hr (whichever comes first)	24 Month or 2000Hr (whichever comes first), Powertrain 36 Month or 2000Hr (whichever comes first)	3 Year Engine and Powertrain Warranty	2 year/ 2000 Hr All inclusive (whichever is first), 3 year/ 2000Hr engine/ Powertrain (whichever is first)	NP	NP	NP	Full 24 month, additional 12 month Powertrain	12 month parts and labor warranty
<b>Notes</b>													
Notes	*wt. with Ag Tires			*field ready, Industrial Tires OPT 12F12R NOTE-Their website no longer lists the MT200B series	*Shipping weight	*Wt. with cab 3968 lbs.	*Lift specs did not say where measured from **Operating weight	OPT 12F12R Power Shuttle *Shipping weight		*Wt without ROPS		*wt. with Ag Tires	

N/A - Not Available

NP - Not Published

OPT - Optional

Manufacturer	KIOTI	TYM	YTO
Model	DK40SE	T400	404
Drive Type	4WD	4WD	4WD
<b>Engine</b>			
Type	4 Cyl. Diesel	4 Cyl. Diesel	3 Cyl. Diesel
Gross HP	41	43	39.4
PTO HP	34	36.5	NP
Displacement Cu.In.	121.98	113	NP
Fuel Capacity Gal.	11.9	9.25	NP
<b>Drive Train</b>			
Clutch	Dry Single	Dry Single	Double Action
Transmission	Syn. Shuttle	Syn. Shuttle	Gear
Speeds	12F12R	12F12R	NP
Differential Lock	STD	NP	NP
Brake Type	Wet Disc	Wet Disc	Wet Disc
PTO Type	Hydro. Indep.	Independent	Live
Rear (RPM)	540	540	540/1000
Mid (RPM)	2000 OPT	N/A	NP
<b>Hydraulic System</b>			
Pump	Gear Tandem	Dual Gear	NP
Total Hydraulic Flow (gpm)	16.8	11.78	NP
3-Point Hitch	Cat. 1	Cat. 1 (with OPT 2)	NP
Lift Capacity at 24" behind lift point Lbs.	2,493	2,105	1,709
Steering	Hydro. Power	Hydro. Power	NP
<b>Dimensions</b>			
Overall Length IN.	134.2	139	139.3
Overall Width IN.	63.9	59.4	65.9
Overall Height IN.	95	95	59.8
Wheel Base IN.	74	71	74.8
Turning Radius FT.	9.5	8.2	13.6
Weight with ROPS Lbs.	4,202*	3,960	4,232
<b>Warranty</b>			
Warranty	4 year (2 Year Bumper to Bumper and 2 year Engine and Drive line)	5 Year (3 Year bumper to Bumper; 4th year Parts & Labor - Drivetrain; 5th year Drivetrain Parts only)	NP
<b>Notes</b>			
Notes	*wt. with Ag Tires		ROPS is optional

N/A - Not Available