

Manufacturer	KIOTI	Bobcat	Case Farmall 40	Challenger	John Deere	Kubota	Massey Ferguson	McCormick	Montana	Montana	New Holland
Model	DK40SE HST	CT440	HST MFD	MT275B HST	4120 HST	L3940HST	1540 HST	CT41HST	3940 HST	R4344 HST	T2310 H
Drive Type	4WD	4WD		4WD	4WD	4WD	4WD	4WD	4WD		FWD
Engine											
Type	4 Cyl. Diesel	Diesel	Diesel	Diesel	4 Cyl. Diesel	4 Cyl. Diesel	3 Cyl. Diesel	4 Cyl. Diesel	4 Cyl. Diesel	4 Cyl. Diesel	4 Cyl. Diesel
Gross HP	41	41	40	40.1	43.1	40.5	40.1	41	39	41	40
PTO HP	32.5	30	33.2	29.5	35	31.5	31	34	NP	34	33.2
Displacement Cu.In.	121.98	122	121.7	91.4	148.9	122	91.4	141.0	109.84	141	121.7
Fuel Capacity Gal.	11.9	11.9	13	10.6	14.5	13.2	10.6	10	10.6	10	13
Drive Train											
Clutch	None	NP	None	Wet Multi Disc	Wet Multi Disc	Dry Single	NP	NP	NP	NP	Wet Disc
Transmission	Hydrostatic	Hydrostatic	Hydrostatic	Hydrostatic	Hydrostatic	Hydrostatic	Hydrostatic	Hydrostatic	Hydrostatic	Hydrostatic	Hydrostatic
Speeds	Inf. 3	Inf. 3	Inf. 2	Inf. 3	Inf. 3	Inf. 3	Inf. 3	Inf. 3	NP	Inf. 3	Inf. 2
Differential Lock	STD	STD	NP	STD	STD	NP	STD	STD	STD	NP	STD
Brake Type	Wet Disc	Wet Disc	Wet Disc	Wet multi Disc	Wet Disc	Wet Disc	Wet multi Disc	Wet Disc	Wet Multi Disc	Wet multi Disc	Wet Disc
PTO Type	Hydro. Indep.	Independent	Independent	Independent	Independent	Independent	Independent	Independent	Independent	Ground (Indep OPT)	Independent
Rear (RPM)	540	540	540	540	540	540	540	540	540	540	540
Mid (RPM)	2000 OPT	2000 OPT	OPT 2000	2000 OPT	2100 OPT	2000 OPT	2000 OPT	OPT	NP	OPT	OPT
Hydraulic System											
Pump	Gear Tandem	NP	Gear	Open Center	Dual Gear	NP	Dual Gear	NP	NP	NP	Gear
Total Hydraulic Flow (gpm)	16.8	16.1	14.9	12.7	17.1	14.7	14	13.7	8.2	12.3	14.9
3-Point Hitch	Cat. 1	Cat. 1	Cat. 1	Cat. 1	Cat. 1	Cat. 1	Cat. 1	Cat. 1	Cat. 1	Cat. 1	Cat. 1
Lift Capacity at 24" behind lift point Lbs.	2,493	1,870	2,330	2,535	2,500	2,756	2,800 at hitch point	2,756 at ball end	2,695 at ball end	2,755 at ball end	2,330
Steering	Hydro. Power	Hydro. Power	Hydro. Power	Hydro. Power	Hydro. Power	Hydro. Power	Hydro. Power	Hydro. Power	Hydro. Power	Hydro. Power	Hydro. Power
Dimensions											
Overall Length IN.	134.2	134.3	125.5	121	128.2	121.5	121	125.7	132	125	125.2
Overall Width IN.	63.9	69	66.6	62.2	90	66.5	62	NP	66	43.3	66.6
Overall Height IN.	95	95.5	95	87.4	97.2	97.4	87.4	95.1	87.5	95	95
Wheel Base IN.	74	73.8	73.5	69.7	71.5	74.6	70	69.2	66.2	69	73.5
Turning Radius FT.	9.5	11	NP	9.2	9.2	8.9	NP	8.4	10.7	8.3	9.2
Weight with ROPS Lbs.	4,130*	3,847*	3,252	3,169*	3,700*	3,627	3,058*	3,583	2,955*	3,582	3,476*
Warranty											
Warranty	4 year (2 Year Bumper to Bumper and 2 year Engine and Drive line)	NP	NP	NP	24 Month or 2000Hr (whichever comes first), Powertrain 36 Month or 2000Hr (whichever comes first)	24 Month or 2000Hr (whichever comes first), Powertrain 36 Month or 2000Hr (whichever comes first)	2 year/ 2000 Hr All inclusive (whichever is first), 3 year/ 2000Hr engine/ Powertrain (whichever is first)	NP	NP	NP	Full 24 month, additional 12 month Powertrain
Notes											
Notes	*wt. with Ag Tires	*wt. with Ag Tires		*field ready, Industrial Tires OPT 12F12R NOTE-Their website no longer lists the MT200B series	*Shipping weight		OPT 12F12R Power Shuttle *Shipping weight		*Wt without ROPS		*Weight with Ag tires

N/A - Not Available

NP - Not Published

OPT - Optional