

Manufacturer	KIOTI	Bobcat	Branson	Case Farmall 45 HST MFD	Challenger	John Deere	Kubota	Massey Ferguson	Massey Ferguson	McCormick	Montana	New Holland
Model	DK45SE HST 4WD	CT445 4WD	4720h 4WD		MT285B HST 4WD	3720 HST 4WD	L4240 HST 4WD	1547 HST 4WD	1643 HST 4WD	CT47HST 4WD	R4944HST	T2320 H FWD
Drive Type	DK45SE HST 4WD	CT445 4WD	4720h 4WD		MT285B HST 4WD	3720 HST 4WD	L4240 HST 4WD	1547 HST 4WD	1643 HST 4WD	CT47HST 4WD	R4944HST	T2320 H FWD
Engine												
Type	4 Cyl. Diesel	Diesel	4 Cyl. Diesel	4 Cyl. Diesel	4 Cyl. Diesel	3 Cyl. Diesel	4 Cyl. Diesel	4 Cyl. Diesel	4 Cyl. Diesel	4 Cyl. Diesel	4 Cyl. Diesel	4 Cyl. Diesel
Gross HP	45	45	47	45	47.5	44	44	47	43.5	47	47	45
PTO HP	36	34	37.8	37.8	36.5	35	35	36.5	33.1	39	39	37.8
Displacement Cu.In.	134.06	134.3	139.5	135.2	134.1	91.5	134.1	134	134.1	152.9	152.9	135.2
Fuel Capacity Gal.	11.9	11.9	9.8	13	13.2	11.8	13.2	13.2	13.2	10	10	13
Drive Train												
Clutch	None	NP	NP	None	Wet Multi Disc	NP	Dry Single	NP	NP	NP	None	Wet Disc
Transmission	Hydrostatic	Hydrostatic	Hydrostatic	Hydrostatic	Hydrostatic	E Hydro	Hydrostatic	Hydrostatic	Hydrostatic	Hydrostatic	Hydrostatic	Hydrostatic
Speeds	Inf. 3	Inf. 3	Inf. 3	Inf. 2	Inf. 3	Inf. 3	Inf. 3	Inf. 3	Inf. 3	Inf. 3	Inf. 3	Inf. 2
Differential Lock	STD	STD	STD	NP	STD	STD	NP	Spiral Bevel	NP	STD	STD	STD
Brake Type	Wet Disc	Wet Disc	Wet Disc	Wet Disc	Wet multi Disc	Wet Multi Disc	Wet Disc	Wet Multi Disc	Wet Multi Disc	Wet Disc	Wet Multi Disc	Wet Disc
PTO Type	Hydro. Indep.	Independent	NP	Independent	Independent	Independent	Independent	Independent	Independent	Independent	Ground (Indep OPT)	Independent
Rear (RPM)	540	540	540/540E	540	540	540	540	540	540	540	540	540
Mid (RPM)	2000 OPT	2000 OPT	N/A	2000 OPT	2000 OPT	2100 OPT	2000 OPT	2000 OPT	2000 OPT	OPT	OPT	OPT
Hydraulic System												
Pump	Gear Tandem	NP	NP	Gear	Open Center	Dual Gear	NP	Dual Gear	Open Center	NP	NP	Open Center
Total Hydraulic Flow (gpm)	16.8	16.1	11.6	14.9	14.9	13.9	14.7	16.5	16.2	13.7	12.3	14.9
3-Point Hitch	Cat. 1	Cat. 1	Cat. 1	Cat. 1	Cat. 1	Cat. 1	Cat. 1	Cat. 1	Cat. 1	Cat. 1	Cat. 1	Cat. 1
Lift Capacity at 24" behind lift point Lbs	2,493	1,870	3,194 at hitch point	2,330	3,086	2,500	2,756	3,483 at hitch point	2,800 at hitch point	2,756 at ball end	2,755 at ball end	2,330
Steering	Hydro. Power	Hydro. Power	Hydro. Power	Hydro. Power	Hydro. Power	Power	Hydro. Power	Hydro. Power	Hydro. Power	Hydro. Power	Hydro. Power	Hydro. Power
Dimensions												
Overall Length IN.	134.2	134.3	124	125.2	132.7	120.2	121.5	132.7	122	125.7	126	125.2
Overall Width IN.	69.2	69	72	66.6	65.4	68.4	66.5	66.1	64.5	NP	43.3	66.6
Overall Height IN.	96.2	95.5	97	95	90	NP	97.4	90.7	103.3	95.1	96	95
Wheel Base IN.	74	73.8	71	73.5	74.8	68	74.6	75	70.9	69.2	69	73.5
Turning Radius FT.	10.2	11	8.5	NP	NP	8.8	8.9	9.2	NP	8.4	8.2	9.2
Weight with ROPS Lbs.	4,189*	3,881*	4,116	3,454*	3,660*	3,570	3,671	3,597*	3,384*	3,583	3,582	3,565*
Warranty												
Warranty	4 year (2 Year Bumper to Bumper and 2 year Engine and Drive line)	NP	4 year limited	NP	NP	24 Month or 2000Hr (whichever comes first), Powertrain 36 Month or 2000Hr (whichever comes first)	24 Month or 2000Hr (whichever comes first), Powertrain 36 Month or 2000Hr (whichever comes first)	2 year/ 2000 Hr All inclusive (whichever is first), 3 year/ 2000Hr engine/ Powertrain (whichever is first)	2 year/ 2000 Hr All inclusive (whichever is first), 3 year/ 2000Hr engine/ Powertrain (whichever is first)	NP	NP	Full 24 month, additional 12 month Powertrain
Notes												
Notes	*wt. with Ag Tires	*wt. with Ag Tires		Wt. with cab 4491 lbs.	*field ready, Industrial Tires NOTE-Their website no longer lists the MT200B series	* Shipping weight.		* Shipping weight.	* Shipping weight.			* Weight with Ag tires

N/A - Not Available

NP - Not Published

OPT - Optional