

Manufacturer Model Drive Type	KIOTI DK50se HST 4WD	Bobcat CT450 4WD	Branson 4720h 4WD	Challenger MT285B HST 4WD	John Deere 4320 HST MFWD	Kubota L4740 HST 4WD	Massey Ferguson 1648 HST 4WD	Massey Ferguson 1652 HST 4WD	Montana R4944 HST 4WD	TYM T503 4WD
<b>Engine</b>										
Type	4 Cyl. Diesel	4 Cyl. Diesel	4 Cyl. Diesel	4 Cyl. Diesel	4 Cyl. Diesel	4 Cyl. Diesel	4 Cyl. Diesel	4 Cyl. Diesel	4 Cyl. Diesel	4 Cyl. Diesel
Gross HP	49	49	47	47.5	48	49	47.1	52.2	47	50.7
PTO HP	37.5	38	37.8	36.5	39.9	41.5	36.5	39.4	41	38.6
Displacement Cu.In.	148.59	156.5	2286cc	134.1	148.9	148.5	134.1	180.4	152.9	135.2
Fuel Capacity Gal.	11.9	11.9	9.8	13.2	14.5	14.3	13.2	13.2	10	17
<b>Drive Train</b>										
Clutch	none	NP	NP	Wet Multi Disc	Wet Disc	Dry Single	NP	NP	NP	Dry Single
Transmission	Hydro.	Hydro.	Hydro.	Hydrostatic	E Hydro	Hydro.	Hydrostatic	Hydrostatic	Hydro.	Sync. Shuttle
Speeds	Inf. - 3	Inf. 3	Inf. 3	Inf. 3	Inf. 3	Inf. 3	Inf. 3	Inf. 3	Inf. 3	16F16R
Differential Lock	STD	STD	STD	STD	STD	STD	NP	NP	STD	STD
Brake Type	Wet Disk Hydraulic, Indepndet	Wet Disc	Wet Disc	Wet multi Disc	Wet Multi Disc	Wet Disc	Wet Multi Disc	Wet Multi Disc	Wet Multi Disc	Wet Disc
PTO Type	Hydraulic, Indepndet	Independent	Independent	Independent	Independent	Independent	Independent	Independent	Ground (Indep OPT)	Independent
Rear (RPM)	540	540	540/540E	540	540	540	540	540	540	580
Mid (RPM)	2000 OPT	2000 OPT	NA	2000 OPT	2100 OPT	2000 OPT	2000 OPT	2000 OPT	OPT	NA
<b>Hydraulic System</b>										
Pump	Gear Tandum	Single or Dual	Position Draft	Open Center	Dual Gear	Position	Open Center	Open Center	NP	Dual Gear
Total Hydraulic Flow (gpm)	16.8	16.1	11.6	14.9	17.1	14.7	16.5	17.7	12.3	14.5
3-Point Hitch	Cat. 1	Cat. 1	Cat. 1	Cat. 1	Cat. 1	Cat. 1	Cat. 1	Cat. 1	Cat. 1	Cat. 1
Lift Capacity at 24" behind lift point Lbs	2,493	1,870	3194 -does not say where from	3,086	2,500	2,760	3,483 at hitch point	3,483 at hitch point	2,755at ball end	2,945
Steering	Hydro. Power	Hydro. Power	Hydro. Power	Hydro. Power	Hydro. Power	Hydro. Power	Hydro. Power	Hydro. Power	Hydro. Power	Hydro. Power
<b>Dimensions</b>										
Overall Length IN.	134.2	134.3	124	132.7	NP	121.5	132.7	132.7	126	141.3
Overall Width IN.	63.9	69	56	65.4	NP	66.5	67.3	67.3	43.3	72.3
Overall Height IN.	95	95.5	97	90	NP	100.6	103.1	103.1	96	101.9
Wheel Base IN.	74	73.8	71	74.8	71.5	74.6	74.8	76	69	76.2
Turning Radius FT.	9.5	11	NP	NP	9.2	8.9	NP	NP	8.2	12.5
Weight with ROPS Lbs.	3,902*	3,935	4,116*	3,660*	3,700*	3,671	3,715*	3,780*	3,582	4,188*
<b>Warranty</b>										
Warranty	4 year (2 Year Bumper to Bumper and 2 year Engine and Drive line)	NP	4 Year Limited	NP	24 Month or 2000Hr (whichever comes first), Powertrain 36 Month or 2000Hr (whichever comes first)	24 Month or 2000Hr (whichever comes first), Powertrain 36 Month or 2000Hr (whichever comes first)	2 year/ 2000 Hr All inclusive (whichever is first), 3 year/ 2000Hr engine/ Powertrain (whichever is first)	2 year/ 2000 Hr All inclusive (whichever is first), 3 year/ 2000Hr engine/ Powertrain (whichever is first)	NP	5 Year (3 Year bumper to Bumper; 4th year Parts & Labor - Drivetrain; 5th year Drivetrain Parts only)
<b>Notes</b>										
Notes	* Wt with Ag Tires	*with Ag tires	*with Ag. Tires	*field ready, Industrial Tires NOTE-Their website no longer lists the MT200B series	*Shipping weight		* Shipping weight.	* Shipping weight.		*with Ag. Tires

N/A - Not Available

NP - Not Published

OPT - Optional

Competitive information contained in this document was obtained from various available sources including websites. As a result, KIOTI does not guarantee or warrant the accuracy of this information.