

Manufacturer	DK50se HST Cabin 4WD	Bobcat CT450 Cab 4WD	Challenger MT285B HST Cab 4WD	John Deere 4320 HST Cab MFWD	Kubota L4740 HSTC 4WD	Massey Ferguson 1648 HST Cab 4WD	Massey Ferguson 1652 HST Cab 4WD	TYM T503 Cab 4WD
Engine								
Type	4 Cyl. Diesel	4 Cyl. Diesel	4 Cyl. Diesel	4 Cyl. Diesel	4 Cyl. Diesel	4 Cyl. Diesel	4 Cyl. Diesel	4 Cyl. Diesel
Gross HP	49	49	47.5	48	49	47.1	52.2	50.7
PTO HP	37.5	38	36.5	39.9	41.5	36.5	39.4	38.6
Displacement Cu.In.	148.59	156.5	134.1	148.9	148.5	134.1	180.4	135.2
Fuel Capacity Gal.	11.9	11.9	13.2	13.8	14.3	13.2	13.2	17
Drive Train								
Clutch	none	NP	Wet Multi Disc	Wet Disc	Dry Single	NP	NP	Dry Single
Transmission	Hydro.	Hydro.	Hydrostatic	E Hydro	Hydro.	Hydrostatic	Hydrostatic	Sync. Shuttle
Speeds	Inf. - 3	Inf. 3	Inf. 3	Inf. 3	Inf. 3	Inf. 3	Inf. 3	16F16R
Differential Lock	STD	STD	STD	STD	STD	NP	NP	STD
Brake Type	Wet Disk	Wet Disc	Wet multi Disc	Wet Multi Disc	Wet Disc	Wet Multi Disc	Wet Multi Disc	Wet Disc
PTO Type	Hydraulic, Indepndet	Independent	Independent	Independent	Independent	Independent	Independent	Independent
Rear (RPM)	540	540	540	540	540	540	540	580
Mid (RPM)	2000 OPT	2000 OPT	2000 OPT	2100 OPT	2000 OPT	2000 OPT	2000 OPT	NA
Hydraulic System								
Pump	Gear Tandum	Single or Dual	Open Center	Dual Gear	Position	Open Center	Open Center	Dual Gear
Total Hydraulic Flow (gpm)	16.8	16.1	14.9	17.1	14.7	17.6	18.9	14.5
3-Point Hitch	Cat. 1	Cat. 1	Cat. 1	Cat. 1	Cat. 1	Cat. 1	Cat. 1	Cat. 1
Lift Capacity at 24" behind lift point Lbs	2,493	1,870	3,086	2,500	2,760	3,483 at hitch point	3,483 at hitch point	2,945
Steering	Hydro. Power	Hydro. Power	Hydro. Power	Hydro. Power	Hydro. Power	Hydro. Power	Hydro. Power	Hydro. Power
Dimensions								
Overall Length IN.	134.2	134.3	132.7	NP	121.5	132.7	132.7	141.3
Overall Width IN.	63.9	69	65.4	NP	66.5	67.3	67.3	72.3
Overall Height IN.	96.7	95.5	90	NP	93.3	90.2	90.2	99.6
Wheel Base IN.	74	73.8	74.8	71.5	74.6	74.8	76	76.2
Turning Radius FT.	9.5	11	NP	9.2	8.9	NP	NP	12.5
Weight with Cabin Lbs.	4,354*	3,935	3,660*	4,345*	4,001	4,068*	4,134*	4,475
Warranty								
Warranty	4 year (2 Year Bumper to Bumper and 2 year Engine and Drive line)	NP	NP	24 Month or 2000Hr (whichever comes first), Powertrain 36 Month or 2000Hr (whichever comes first)	24 Month or 2000Hr (whichever comes first), Powertrain 36 Month or 2000Hr (whichever comes first)	2 year/ 2000 Hr All inclusive (whichever is first), 3 year/ 2000Hr engine/ Powertrain (whichever is first)	2 year/ 2000 Hr All inclusive (whichever is first), 3 year/ 2000Hr engine/ Powertrain (whichever is first)	5 Year (3 Year bumper to Bumper; 4th year Parts & Labor - Drivetrain; 5th year Drivetrain Parts only)
Notes								
Notes	*WT with Ag tires	*with Ag tires	*field ready, ROPS, Industrial tires NOTE-Their website no longer lists the MT200B series	*Shipping weight		* Shipping weight.	* Shipping weight.	

N/A - Not Available

NP - Not Published

OPT - Optional

Competitive information contained in this document was obtained from various available sources including websites. As a result, KIOTI does not guarantee or warrant the accuracy of this information.