

Manufacturer Model Drive Type	KIOTI DK55 4WD	Branson 5530 4WD	Case Farmall 55 MFD	Challenger 315B 4WD	Deutz-Fahr Agrolux 57	John Deere 4520 4WD	John Deere 5225 MFWD	Kubota L5040 GST 4WD	Mahindra 5500 4WD	Massey Ferg 1655 SS 4WD	McCormick CT65U 4WD	Montana 5740 4WD
Engine												
Type	4 Cyl. Diesel	4 Cyl. Diesel	4 Cyl. Diesel	3 Cyl. Diesel	3 Cyl. Diesel	4 Cyl. Diesel	5 Cyl Diesel	4 Cyl. Diesel	4 Cyl. Diesel	4 Cyl. Diesel	4 Cyl. Diesel	4 Cyl. Diesel
Gross HP	54	55	55	58	55	53.1	56	52	54	55.4	57	57
PTO HP	45.2	47	46	45	52	45.5	45	44	44	43	50	NP
Displacement Cu.In.	134.1	139.5	135.2	201	183	148.9	186	148.5	186.4	180.4	NP	203.3
Fuel Capacity Gal.	18	24	13.5	29	14	14.5	33.5	14.3	17.1	13.2	15.85	15.9
Drive Train												
Clutch	Dry Single	Dry Single	Dry	NP	Dry Single	Wet Multi Syn Shuttle	Dry	Dry Single	Dry	Wet Multi	Dry Single	NP
Transmission	Syn. Shuttle	Syn. Shuttle	Syn. Shuttle	Syn. Shuttle	Syn. Shuttle	Syn. Shuttle Power Rev	Syn. Shuttle	GST	Syn. Shuttle	Syn. Shuttle	Mech. Shuttle	Syn. Shuttle
Speeds	12F12R	24F24R	12F12R	12F12R	20F10R	12F12R	9F3R	12F8R	8F8R	8F8R	16F16R	16F16R
Differential Lock	STD	STD	STD	STD	STD	STD	STD	NP	NP	STD	STD	STD
Brake Type	Wet Disc	Wet Disc	Wet Disc	Wet Disc	Wet Disc	Wet Disc	Wet Disc	Wet Disc	Wet Disc	Wet Multi Disc	Wet Multi Disc	Wet Multi Disc
PTO Type	Live	Independent	Independent	Independent	Independent	Independent	Independent	Independent	Independent	Independent	Independent	Independent
Rear (RPM)	540 (1000 OPT)	540/680/1000	540	540	540/540E (1000 OPT)	540	540	540	540/1000	540	NP	540
Mid (RPM)	NP	NP	NP	NP	NP	2100 OPT	NP	2000 OPT	NP	NA	NP	NP
Hydraulic System												
Pump	Gear Tandem	Open Center	Gear	Gear	Gear	Dual Gear	Dual Gear	NP	Open Center	Open Center	NP	NP
Total Hydraulic Flow (gpm)	9.88	NP	16.95	15.8	16.5	17.1	19.4	14.1	11	17.7	14.1	8.7 valve flow rated only
3-Point Hitch	Cat. 1	Cat. 1	Cat. 1 & 2	Cat. 1 & 2	Cat. 2	Cat. 1	Cat. 1 & 2	Cat. 1 & 2	Cat. 1 & 2	Cat. 1	Cat. 2	Cat. 1
Lift Capacity at 24" behind lift point Lbs	2,654	NP	3,465	5,500 at link end	6,600 at lift point	2,500	3,374	2,976	3,968*	3,483 at hitch point	3,860 at ball end	3,527 at ball end
Steering	Hydro. Power	Hydro. Power	Hydro. Power	Hydro. Power	Hydro. Power	Hydro. Power	Hydro. Power	Hydro. Power	Hydro. Power	Hydro. Power	Hydro. Power	Hydro. Power
Dimensions												
Overall Length IN.	130.5	143.6	137.3	148	121.5	128.2	142	126.4	150	132.7	NP	142
Overall Width IN.	69.3	74	64.4	76	80.3	90	71	67.3	77.4	67.3	NP	68.6
Overall Height IN.	101.5	100	95	105	90.1	97.2	94	101	NP	103.1	NP	98
Wheel Base IN.	75.6	80	74.8	82.7	76	71.5	85.8	75.4	83	76	NP	81.7
Turning Radius FT.	9.6	NP	NP	NP	11.8	9.8	10.2	9.2	11.5	NP	NP	10.5
Weight with ROPS Lbs.	4,795*	5,090	4,209	5,732	5,247*	3,700*	6,030*	3,803	6,230	3,770*	4,770	4,650*
Warranty												
Warranty	4 year (2 Year Bumper to Bumper and 2 year Engine and Drive line)	4 year limited	NP	NP	NP	24 Month or 2000Hr (whichever comes first), Powertrain 36 Month or 2000Hr (whichever comes first)	24 Month or 2000Hr (whichever comes first), Powertrain 36 Month or 2000Hr (whichever comes first)	24 Month or 2000Hr (whichever comes first), Powertrain 36 Month or 2000Hr (whichever comes first)	3 Year Engine and Powertrain Warranty	2 year/ 2000 Hr All inclusive (whichever is first), 3 year/ 2000Hr engine/ Powertrain (whichever is first)	NP	NP
Notes												
Notes	*wt. with Ag Tires		12x12 Power Shuttle option	OP 12F12R Power Shuttle	*Shipping weight	OPT Twin Touch Ehydro, Inf 3 *Shipping weight	OPT 12F12R or 24R24R PowrReverser; Clutch Wet *Shipping weight		*Lift specs did not say where measured from		*Shipping weight	*Weight w/o ROPS

N/A - Not Available

NP - Not Published

OPT - Optional

Manufacturer Model Drive Type	KIOTI DK55 4WD	New Holland T2410 FWD	TYM T603 4WD	YTO 554 4WD
Engine				
Type	4 Cyl. Diesel	4 Cyl. Diesel	4 Cyl. Diesel	4 Cyl. Diesel
Gross HP	54	55	58	54.3
PTO HP	45.2	47	46.6	NP
Displacement Cu.In.	134.1	135.2	135.2	NP
Fuel Capacity Gal.	18	13.5	18.5	NP
Drive Train				
Clutch	Dry Single	Dry Disc	Dry Single	Double Action Plantetary
Transmission	Syn. Shuttle	Syn shuttle	Syn. Shuttle	Gear
Speeds	12F12R	12F12R	24F24R	NP
Differential Lock	STD	STD	NP	NP
Brake Type	Wet Disc	Wet Disc	Wet Disc	Wet Disc
PTO Type	Live	Independent	Independent	Semi-Independent
Rear (RPM)	540 (1000 OPT)	540	540/1000	540/1000
Mid (RPM)	NP	NP	N/A	NP
Hydraulic System				
Pump	Gear Tandem	Gear	Dual gear	NP
Total Hydraulic Flow (gpm)	9.88	163.9	15.1	NP
3-Point Hitch	Cat. 1	Cat. 1 & 2	Cat. 2	NP
Lift Capacity at 24" behind lift point Lbs	2,654	3,465	2,528	2,023
Steering	Hydro. Power	Hydro. Power	Hydro. Power	NP
Dimensions				
Overall Length IN.	130.5	137.3	159	152.8
Overall Width IN.	69.3	71.6	71	67.5
Overall Height IN.	101.5	91.4	98	67.7
Wheel Base IN.	75.6	74.8	83	83.7
Turning Radius FT.	9.6	9.2	9.2	14.1
Weight with ROPS Lbs.	4,795*	4,260*	5,204	4,365
Warranty				
Warranty	4 year (2 Year Bumper to Bumper and 2 year Engine and Drive line)	Full 24 month, additional 12 month Powertrain	5 Year (3 Year bumper to Bumper; 4th year Parts & Labor - Drivetrain; 5th year Drivetrain Parts only)	NP
Notes				
Notes	*wt. with Ag Tires	*Shipping weight		*ROPS is optional

N/A - Not Available