

Manufacturer	KIOTI	Case Farmall 80	Challenger	Deutz-Fahr	John Deere	Kubota	Mahindra	Massey Ferg	McCormick	Montana	New Holland
Model	DK75	Cab	MT335B Cab	Agrolux 57	5425 Cab	M7040 Cab	7010Cab	3635 Cab	CX75 Cab	P7084C	T4030
Drive Type	4WD	MFD	4WD		4WD	4WD	4WD	4WD	4WD	4WD	FWD
Engine											
Type	4 Cyl. Diesel	4 Cyl. Diesel	3 Cyl. Diesel	3 Cyl. Diesel	4 Cyl. Diesel	4 Cyl. Diesel	4 Cyl. Diesel	3 Cyl. Diesel	4 Cyl. Diesel	4 Cyl. Diesel	4 Cyl. Diesel
Gross HP	74.4	72	78	70	81	71	72	78	73	72	76
PTO HP	58.4	62	65	67	66.25	62	63	65	60	55	62
Displacement Cu.In.	268.5	238	201	183	276	203	194.7	201	268	195-T	195
Fuel Capacity Gal.	33	23.8	29	14	22.5	23.8	26.4	29	41	26.4	21.6
Drive Train											
Clutch	Dry Single	Dry	NP	Dry Single	Dry	Dry	Dry	Dry Single	Wet	NP	Dry
Transmission	Syn. Shuttle	Mech Shuttle	Syn. Shuttle	Syn. Shuttle	Syn. Shuttle	Syn. Shuttle	Syn. Shuttle	Syn. Shuttle	Syncromesh	Syn. Shuttle	Mech Shuttle
Speeds	12F12R	12F12R	12F12R	20F10R	9F3R	8F8R	16F16R	8F8R	8F8R	12F12R	12F12R
Differential Lock	STD	STD	STD	STD	STD	STD	NP	STD	NP	NP	NP
Brake Type	Wet Disc	Wet Disc	Wet Disc	Wet Disc	Wet Disc	Wet Disc	Wet Disc	Wet Multi Disc	Wet Disc	Hydraulic	Wet Disc
PTO Type	Hydro. Indep.	Independent	Independent	Independent	Independent	Independent	Independent	Independent	Independent	Independent	Independent
Rear (RPM)	540 STD	540 (1000 OPT)	540	540/540E (1000 OPT)	540 (1000 OPT)	540	540/1000	540	540/1000	540/750/1000	540 (1000 OPT)
Mid (RPM)	N/A	N/A	N/A	NP	NP	NP	NP	N/A	NP	NP	NP
Hydraulic System											
Pump	Gear Tandem	Open Center	Gear	Gear	Open Center	Open Center	Open Center	Gear	Gear	Mechanical	Gear
Total Hydraulic Flow (gpm)	12.3	13.6	15.8	16.5	18.7	11	12.4	22.4	15.7	19	20.2
3-Point Hitch	Cat. 2	Cat. 2	Cat. 1 & 2	Cat. 2	Cat. 1 & 2	Cat. 1 & 2	Cat. 2	Cat. 1 & 2	Cat. 2	NP	Cat. 1 & 2
Lift Capacity at 24" behind lift point Lbs	5,290	5,025	5,500 at link end	6,600 at lift point	3,374	3,307	4,329	5,512 at hitch point	4,347 at link end	5,511*	3,962
Steering	Hydro. Power	Hydro. Power	Hydro. Power	Hydro. Power	Hydro. Power	Hydro. Power	Hydro. Power	Hydro. Power	Hydro. Power	NP	Hydro. Power
Dimensions											
Overall Length IN.	159.8	NP	148	129	NP	136	153.4	148	157.7	157	135.2
Overall Width IN.	78.7	69.6	76	86	NP	73	76	76	84.5	77.8	NP
Overall Height IN.	111	103.1	102.5	92	NP	100.2	NP	101.2	106.6	102	91.4
Wheel Base IN.	90.7	87	82.7	80.9	85.7	82.1	NP	81.9	93.3	86.6	83.3
Turning Radius FT.	12.4	NP	NP	11.8	11.6	11.8	12.8	NP	14.4	10.7	NP
Weight with CAB Lbs.	7,749*	6,915*	7,716	5,644	7,385*	4,608*	6,254*	7,056*	8,289*	7,293	6,768*
Warranty											
Warranty	4 year (2 Year Bumper to Bumper and 2 year Engine and Drive line)	NP	NP	NP	24 Month or 2000Hr (whichever comes first), Powertrain 36 Month or 2000Hr (whichever comes first)	24 Month or 2000Hr (whichever comes first), Powertrain 36 Month or 2000Hr (whichever comes first)	3 Year Engine and Powertrain Warranty	2 year/ 2000 Hr All inclusive (whichever is first), 3 year/ 2000Hr engine/ Powertrain (whichever is first)	NP	NP	Full 24 month, additional 12 month Powertrain
Notes											
Notes	*wt. with Ag Tires		OPT 12F12R Power Shuttle		OPT 12F12R *Shipping weight	*Wt with ROPS not cab and Ag tires	*Operating weight with standard front weights	OPT 12F12R Power Shuttle *Shipping weight	*Weight with standard equipment	*did not say where from	*Shipping weight with Ag tires

N/A - Not Available

NP - Not Published

OPT - Optional

Competitive information contained in this document was obtained from various available sources including websites. As a result, KIOTI does not guarantee or warrant the accuracy of this information.

Manufacturer	KIOTI	TYM
Model	DK75	T700 Cab
Drive Type	4WD	4WD
Engine		
Type	4 Cyl. Diesel	3 Cyl. Diesel
Gross HP	74.4	70
PTO HP	58.4	63.5
Displacement Cu.In.	268.5	179
Fuel Capacity Gal.	33	27.9
Drive Train		
Clutch	Dry Single	Dry Single
Transmission	Syn. Shuttle	Syn. Shuttle
Speeds	12F12R	16F16R
Differential Lock	STD	NP
Brake Type	Wet Disc	Wet Disc
PTO Type	Hydro. Indep.	Independent
Rear (RPM)	540 STD	540
Mid (RPM)	N/A	N/A
Hydraulic System		
Pump	Gear Tandem	Dual Gear
Total Hydraulic Flow (gpm)	12.3	15.6
3-Point Hitch	Cat. 2	Cat. 2
Lift Capacity at 24" behind lift point Lbs	5,290	2,950
Steering	Hydro. Power	Hydro. Power
Dimensions		
Overall Length IN.	159.8	159.4
Overall Width IN.	78.7	77.1
Overall Height IN.	111	102.3
Wheel Base IN.	90.7	83.2
Turning Radius FT.	12.4	12.8
Weight with CAB Lbs.	7,749*	6,660
Warranty		
Warranty	4 year (2 Year Bumper to Bumper and 2 year Engine and Drive line)	5 Year (3 Year bumper to Bumper; 4th year Parts & Labor - Drivetrain; 5th year Drivetrain Parts only)
Notes		
Notes	*wt. with Ag Tires	

N/A - Not Available