

## FRONT END LOADERS



# KL130

\* Specifications may vary with tractor model, front axle configurations, tire size option and type of attachment, and are subject to change without notification.

### STANDARD FEATURE

- Arched low profile maximizes operator's visibility and is well matched with unique hood style.
- Entire loader except mounting is quick-detached from tractor.
- A built-in parking stand on the front end loader provides quick and easy connection.
- Bucket level indicator is standard.
- Mid mount style frame for engine accessibility.
- Color compliments tractor.

### SPECIFICATIONS

MODEL	KL130
▶Ballast Box attached to 3-point	700 lbs.
▶A - Maximum Lift Height	92.5"
▶B - Clearance with Attachment Level	85.7"
▶C - Clearance with Attachment Dumped	73.6"
▶D - Reach at Maximum Height	17.8"
▶E - Maximum Dump Angle	52°
▶F - Reach with Attachment on Ground	55.7"
▶G - Attachment Rollback Angle	35°
▶H - Digging Depth Below Grade	5.31"
▶J - Overall Height in Carry Position	47.64"
▶L - Depth of Attachment (to back of inner shell)	17.71"
▶M - Height of Attachment	18.50"
▶N - Depth of Attachment (to pivot pin)	19.5"
▶U- Lift Capacity to Full Height @ Pivot Pins	1155 lbs
▶Y- Breakout Force @ Pivot Pin	2046 lbs
▶Relief Valve Setting (Loader Control Valve)	2,000 psi
▶Rated Flow (Tractor System)	2.7 GPM
▶Approximate Weight /bucket	770 lbs
▶Lift Cylinders	1.75"x21.5"
▶Bucket Cylinder	1.75"x18.25"
▶Attachment used for Specification	60"
▶Cycle Times	2,900 (Full)
▶Raise Boom	3.9

▶Lower Boom	2.8
▶Dump Bucket	2.7
▶Retract Bucket	2.4
▶Hydraulic System	Tractor pump w/ loader control valve

### APPLICATION CHART

FEL	Bucket	DS Series		CK Series				DK Series							LK Series		
		4110	4510	20S	27	30	35	35SE	40SE	45SE	50SE	55	75	90	30 (TLB)		
KL1231	50"																<b>X</b>
KL120	60"			<b>X</b>													
KL130	60"				<b>X</b>	<b>X</b>	<b>X</b>										
KL351	66"							<b>X</b>									
KL401	72"								<b>X</b>	<b>X</b>	<b>X</b>						
KL402	72"	<b>X</b>	<b>X</b>														
KL451	72"									<b>X</b>	<b>X</b>						
KL551	78"											<b>X</b>					
KL901	84"												<b>X</b>	<b>X</b>			