

FRONT END LOADERS



KL402

✱ Specifications may vary with tractor model, front axle configurations, tire size option and type of attachment, and are subject to change without notification.

STANDARD FEATURE

- Loader specifically designed for KIOTI DS Series Tractors.
- Efficient performance with single joystick control.
- Designed to be quickly and easily attached and detached.

SPECIFICATIONS

MODEL	KL402
▶A - Maximum Lift Height	107.8"
▶B - Clearance with Attachment Level	105.5"
▶C - Clearance with Attachment Dumped	79.9"
▶D - Reach at Maximum Height	16.1"
▶E - Maximum Dump Angle	73°
▶F - Reach with Attachment on Ground	73.6"
▶G - Attachment Rollback Angle	42°
▶H - Digging Depth Below Grade	6.7"
▶I - Overall Height in Carry Position	52.7"
▶J - Depth of Attachment (to back of inner shell)	20.7"
▶K - Height of Attachment	22.6"
▶L- Lift Capacity to Full Height @ Pivot Pins	2761 lbs
▶M- Breakout Force @ Pivot Pin	3727 lbs
▶Relief Valve Setting (Loader Control Valve)	2,556 psi
▶Rated Flow (Tractor System)	10 GPM
▶Bucket Rollback Force at Ground Line	2990 lbs

APPLICATION CHART

FEL	Bucket	DS Series		CK Series				DK Series							LK Series		
		4110	4510	20S	27	30	35	35SE	40SE	45SE	50SE	55	75	90	30 (TLB)		
KL1231	50"																X
KL120	60"			X													
KL130	60"				X	X	X										
KL351	66"							X									
KL401	72"								X	X	X						
KL402	72"	X	X														
KL451	72"									X	X						
KL551	78"											X					
KL901	84"												X	X			