

DK35-HSTC

Specifications



Engine	
▶ Engine Model	3B183LWH
▶ Engine Gross Power	38 HP (28.3KW)
▶ Rated Speed	2,600 rpm
▶ No. of Cylinder	3
▶ Fuel Type	Diesel
▶ Aspiration	Natural
▶ Displacement	111.43 cu.in. (1,826 cc)
▶ Fuel Tank Capacity	11.9 gal (45L)
▶ Pre-heating System	Glow Plugs
Transmission	
▶ Transmission Type	Hydrostatic
▶ Shuttle	N/A
▶ Main Gear	Hydrostatic
▶ No. of Travel Speed Forward / Reverse	3 Range HST
▶ Min. Travel Speed of Forward w/ Ag1 @ Engine rated speed	0 mph (0 kph)
▶ Max. Travel Speed of Forward w/ Ag1 @ Engine rated speed	14.9 mph (24 kph)
Power Take-Off	
▶ PTO Type Trans	Hydraulic, Independent
▶ PTO Power	27 HP (ROPS)/ 26.1 HP (Cab)
▶ Rear PTO Speeds(1st)	540 rpm
▶ Rear PTO Speeds(2nd)	N/A
▶ Mid PTO Speeds	2,000 rpm (Optional)
▶ Front PTO Speeds	
Brakes and Clutch	
▶ Brakes	Wet disc




▶Clutch	N/A
Dimensions w/ AG Tire	
▶Length w/ 3-point hitch	129.1 in. (3,280 mm)
▶Width	61.6 in. (1,565 mm)
▶Height from Top of ROPS	
▶Height from Top of ROPS Cab	95.5 in. (2,425 mm)
▶Height from Top of ROPS Folded	
▶From Top of the Highest Point	
▶Wheelbase	69.5 in. (1,767 mm)
▶Ground Clearance	14.3 in. (365 mm)
▶Front Tread Ag Tires - Min	49.1 in. (1,248 mm)
▶Front Tread Ag Tires - Max	
▶Rear Tread Ag Tires - Min	48.7 in. (1,237 mm)
▶Rear Tread Ag Tires - Max	53.0 in. (1,347 mm)
▶Turning Radius w/ Brake	9.3 ft (2.85 m)
▶Turning Radius w/o Brake	
Hydraulics	
▶Total Pump Flow	15.2 gpm (57.8(L/min)
▶Main Pump Capacity	
▶Power Steering Pump Capacity	
3-Point Hitch	
▶Standard Category (Optional Category)	Cat. I (N/A)
▶Lift Capacity, 24" aft of hitch, lb(kg)	2,383 lbs (1,081 kg)
▶Control Type	Position, Draft, Mixed control
Weight	
▶Weight w/ Ag Tires w/ Cab	4,351 lbs. (1,973 kg)

▶Equipment & Panel

Standard Equipment	Optional Equipment	Instrument Panel
Telescopic 3 Point Hitch Ends	2nd. Remote Hydraulic Valve	Tachometer with Hour meter
Telescopic Stabilizers	Rear & Front Weights	Fuel Gauge

Crank Adjustable Lift Link	Sunshade	Coolant Temperature Gauge
Single Lever Joy Stick For Loader Operation	Mid PTO	PTO Operation Indicator
Foldable ROPS	Trailer Outlet (7 Pin Socket)	Battery Charge indicator
Hydrostatic Power Steering		Low Oil Pressure Indicator
Rear Differential Lock		Glow Operation Indicator
Foot Throttle (Mechanical)		4WD Operation Indicator
Removable Drawbar		Shuttle Neutral Indicator
Adjustable Seat with Seat Belt		Parking Brake Operation Indicator
Head Lights		Cruise Operation Indicator
Safety Light		
Tilt Steering Wheel		
Wet Disc Brake		
Oil Cooler		
Air Conditioner/ Heater (Cab only)		
CD play with Radio (Cab only)		
Sunvisor (Cab only)		
Cup Holder (Cab only)		

›Tires

 Ag	▶Ag1 4WD Front	7-16/6
	▶Ag1 4WD Rear	12.4-24/6
	▶Ag2 4WD Front	N/A
	▶Ag2 4WD Rear	N/A
 Turf	▶Turf1 4WD Front	27x8.5-15/4
	▶Turf1 4WD Rear	41x14-20/4
	▶Turf2 4WD Front	N/A
	▶Turf2 4WD Rear	N/A
 Ind	▶Ind1 4WD Front	27x10.5-15/6
	▶Ind1 4WD Rear	43x16-20/4
	▶Ind2 4WD Front	N/A
	▶Ind2 4WD Rear	N/A

›Attachments

Front End Loaders	▶KL351 ,
Backhoes	▶KB2475 , KB2485 ,

›Implements

Mowers	▶KMR03-72 , KMR03-84 ,
Tillers	▶KT03-59 , KT09-65 ,