

DK35SE

Specifications



Engine	
▶ Engine Model	3B183LWM
▶ Engine Gross Power	38 HP (28.3 KW)
▶ Rated Speed	2,600 rpm
▶ No. of Cylinder	3
▶ Fuel Type	Diesel
▶ Aspiration	Natural
▶ Displacement	111.43 cu.in. (1,826 cc)
▶ Fuel Tank Capacity	11.9 gal (45 L)
▶ Pre-heating System	Glow Plugs
Transmission	
▶ Transmission Type	Manual
▶ Shuttle	Synchronized
▶ Main Gear	Synchronized
▶ No. of Travel Speed Forward / Reverse	F12/R12
▶ Min. Travel Speed of Forward w/ Ag1 @ Engine rated speed	0.9 mph (1.4 kph)
▶ Max. Travel Speed of Forward w/ Ag1 @ Engine rated speed	15.0 mph (24.2 kph)
Power Take-Off	
▶ PTO Type Trans	Hydraulic, Independent
▶ PTO Power	28.5 HP (21.2 KW)
▶ Rear PTO Speeds(1st)	540 rpm
▶ Rear PTO Speeds(2nd)	N/A
▶ Mid PTO Speeds	2,000 rpm (optional)
▶ Front PTO Speeds	
Brakes and Clutch	
▶ Brakes	Wet disc




▶Clutch	Dry single stage
Dimensions w/ AG Tire	
▶Length w/ 3-point hitch	129.1 in. (3,280 mm)
▶Width	61.6 in. (1,565 mm)
▶Height from Top of ROPS	93.1 in. (2,365 mm)
▶Height from Top of ROPS Cab	N/A
▶Height from Top of ROPS Folded	
▶From Top of the Highest Point	93.1 in. (2,365 mm)
▶Wheelbase	69.5 in. (1,767 mm)
▶Ground Clearance	14.3 in. (365 mm)
▶Front Tread Ag Tires - Min	49.0 in. (1,245 mm)
▶Front Tread Ag Tires - Max	
▶Rear Tread Ag Tires - Min	48.7 in. (1,237 mm)
▶Rear Tread Ag Tires - Max	53.0 in. (1,347 mm)
▶Turning Radius w/ Brake	9.3 ft. (2.85 m)
▶Turning Radius w/o Brake	
Hydraulics	
▶Total Pump Flow	15.2 gpm (57.8 Lpm)
▶Main Pump Capacity	
▶Power Steering Pump Capacity	
3-Point Hitch	
▶Standard Category (Optional Category)	Cat. I (N/A)
▶Lift Capacity, 24" aft of hitch, lb(kg)	2,383 lbs. (1,081 kg)
▶Control Type	Position, Draft, Mixed control
Weight	
▶Weight w/ Ag Tires w/ ROPS	3,963 lbs.(1,798 kg)
▶Weight w/ Ag Tires w/ Cab	N/A

▶Equipment & Panel

Standard Equipment	Optional Equipment	Instrument Panel
Telescopic 3 Point Hitch Ends	2nd. Remote Hydraulic Valve Tachometer with Hour meter	

Telescopic Stabilizers Crank Adjustable Lift Link Single Lever Joy Stick For Loader Operation Foldable ROPS Hydrostatic Power Steering Rear Differential Lock Foot Throttle (Mechanical) Removable Drawbar Adjustable Seat with Seat Belt Head Lights Safety Light Tilt Steering Wheel Wet Disc Brake	Rear & Front Weights Sunshade Mid PTO Trailer Outlet (7 Pin Socket)	Fuel Gauge Coolant Temperature Gauge PTO Operation Indicator Battery Charge indicator Low Oil Pressure Indicator Glow Operation Indicator 4WD Operation Indicator Shuttle Neutral Indicator Parking Brake Operation Indicator
---	--	---

›Tires

 Ag	›Ag1 4WD Front	7-16/6
	›Ag1 4WD Rear	12.4-24/6
	›Ag2 4WD Front	N/A
	›Ag2 4WD Rear	N/A
 Turf	›Turf1 4WD Front	27 x 8.5-15/4
	›Turf1 4WD Rear	41 x 14-20/4
	›Turf2 4WD Front	N/A
	›Turf2 4WD Rear	N/A
 Ind	›Ind1 4WD Front	27 x 10.5-15/6
	›Ind1 4WD Rear	43 x 16-20/4
	›Ind2 4WD Front	N/A
	›Ind2 4WD Rear	N/A

›Attachments

Front End Loaders	›KL351 ,
Backhoes	›KB2475 , KB2485 ,

›Implements

Mowers	›KMR03-72 , KMR03-84 ,
Tillers	›KT03-59 , KT09-65 ,