

# DK55C

## Specifications






| Engine   |                         |
|--|-------------------------|
| » Engine Model   | 4A220TLWB               |
| » Engine Gross Power                                       | 54 HP (40.3 KW)         |
| » Rated Speed  | 2,600 rpm               |
| » No. of Cylinder  | 4                       |
| » Fuel Type  | Diesel                  |
| » Aspiration   | Turbocharged            |
| » Displacement   | 134.1 cu.in. (2,197 cc) |
| » Fuel Tank Capacity                                       | 18 gal (68 L)           |
| » Pre-heating System                                       | Glow plugs              |
| Transmission   |                         |
| » Transmission Type  | Manual                  |
| » Shuttle  | Synchronized            |
| » Main Gear  | Synchronized            |
| » No. of Travel Speed Forward / Reverse                    | 12F/12R                 |
| » Min. Travel Speed of Forward w/ Ag1 @ Engine rated speed | 0.24 mph (0.39 kph)     |
| » Max. Travel Speed of Forward w/ Ag1 @ Engine rated speed | 16.42 mph (26.43 kph)   |
| Power Take-Off   |                         |
| » PTO Type Trans   | Independent             |
| » PTO Power  | 45.2 HP (33.9 KW)       |
| » Rear PTO Speeds(1st)                                     | 540 rpm                 |
| » Rear PTO Speeds(2nd)                                     | 1,000 rpm               |
| » Mid PTO Speeds   | N/A                     |
| » Front PTO Speeds   | Same as Engine Speed    |
| Brakes and Clutch  |                         |
| » Brakes   | Wet Disc                |
| » Clutch   | Dry Single Plate        |

| Dimensions w/ AG Tire                    |                           |
|--|---------------------------|
| ▶Length w/ 3-point hitch                 | 130.5 in. (3,316 mm)      |
| ▶Width                                   | 69.3 in. (1,760 mm)       |
| ▶Height from Top of Cab                  | 99.6 in. (2,530)          |
| ▶From Top of the Highest Point           |                           |
| ▶Wheelbase                               | 75.6 in. (1,920 mm)       |
| ▶Ground Clearance                        | 17.5 in. (445 mm)         |
| ▶Front Tread Ag Tires - Min              | 57.5 in. (1,461 mm)       |
| ▶Front Tread Ag Tires - Max              |                           |
| ▶Rear Tread Ag Tires - Min               | 53.9 in. (1,370 mm)       |
| ▶Rear Tread Ag Tires - Max               | 61.6 in. (1,564 mm)       |
| ▶Turning Radius w/ Brake                 | 9.6 ft. (2.92 m)          |
| ▶Turning Radius w/o Brake                | 11.7 ft. (3.56 m)         |
| Hydraulics                               |                           |
| ▶Total Pump Flow                         | 14.2 gpm (53.8 Lpm)       |
| ▶Main Pump Capacity                      | 9.9 gpm (37.4 Lpm)        |
| ▶Power Steering Pump Capacity            | 4.3 gpm (16.4 Lpm)        |
| 3-Point Hitch                            |                           |
| ▶Standard Category (Optional Category)   | Cat. 2 (1)                |
| ▶Lift Capacity, 24" aft of hitch, lb(kg) | 2,866 lbs. (1,300 kg)     |
| ▶Control Type                            | Position, Draft and Mixed |
| Weight                                   |                           |
| ▶Weight w/ Ag Tires w/ Cab               | 5,180 lbs. (2,350kg)      |

## Equipment & Panel

| Standard Equipment  | Optional Equipment                              | Instrument Panel   |
|---|---|--|
| Foldable ROPS<br>Hydrostatic Power Steering<br>Rear Differential Lock<br>Wet Disc Brakes<br>Hand & Foot Throttles<br>Swing Drawbar<br>Adjustable Seat with Seat belt<br>Headlights<br>Safety Lights<br>Safety Start Switch<br>Rear Working Light<br>Dual Remote Hydraulic Valve<br>Pre Cleaner (Cab only)<br>Flip up PTO Guard<br>Foot-operated Tilt Steering Wheel<br>Full Open Hood<br>Telescopic Lower Link Ends<br>Telescopic stabilizer<br>Crank type lift rod<br>Bevel gear front wheel drive<br>4WD indicator<br>Single lever joystick<br>Side mount hydraulic couplers<br>Tool Box<br>Cup holder<br>Trailer electrical outlet | Sunshade<br>Front PTO<br>Front suitcase weights | Tachometer with Hour Meter<br>Tachometer Gauge<br>Fuel Gauge<br>Temperature Gauge<br>Oil Pressure Indicator<br>PTO Indicator<br>Low Fuel Indicator<br>Hydraulic Warning<br>Glow Plug Indicator<br>Separate Detector<br>Low Coolant Indicator |

## >Tires

|   |                  |              |
|---|------------------|--------------|
| <br>Ag   | ▶Ag1 4WD Front   | 9.5x20/6     |
|   | ▶Ag1 4WD Rear    | 14.9x28      |
|   | ▶Ag2 4WD Front   | N/A          |
|   | ▶Ag2 4WD Rear    | N/A          |
| <br>Turf | ▶Turf1 4WD Front | 29x12.5x15/4 |
|   | ▶Turf1 4WD Rear  | 44x18-20     |
|   | ▶Turf2 4WD Front | N/A          |
|   | ▶Turf2 4WD Rear  | N/A          |
| <br>Ind  | ▶Ind1 4WD Front  | 14x17.5      |
|   | ▶Ind1 4WD Rear   | 18.4x24/8    |
|   | ▶Ind2 4WD Front  | N/A          |
|   | ▶Ind2 4WD Rear   | N/A          |

›Attachments

|                                   |          |
|-----------------------------------|----------|
| <a href="#">Front End Loaders</a> | ›KL551 , |
|-----------------------------------|----------|

›Implements

|                         |                      |
|-------------------------|----------------------|
| <a href="#">Mowers</a>  | ›KMR03-84 ,          |
| <a href="#">Tillers</a> | ›KT03-65 , KT03-73 , |