

# DK55

## Specifications






Engine	
▶ Engine Model	4A220TLWB
▶ Engine Gross Power	54 HP (40.3 KW)
▶ Rated Speed	2,600 rpm
▶ No. of Cylinder	4
▶ Fuel Type	Diesel
▶ Aspiration	Turbocharged
▶ Displacement	134.1 cu.in. (2,197 cc)
▶ Fuel Tank Capacity	18 gal (68 L)
▶ Pre-heating System	Glow plugs
Transmission	
▶ Transmission Type	Manual
▶ Shuttle	Synchronized
▶ Main Gear	Synchronized
▶ No. of Travel Speed Forward / Reverse	12F/12R
▶ Min. Travel Speed of Forward w/ Ag1 @ Engine rated speed	0.24 mph (0.39 kph)
▶ Max. Travel Speed of Forward w/ Ag1 @ Engine rated speed	16.42 mph (26.43 kph)
Power Take-Off	
▶ PTO Type Trans	Independent
▶ PTO Power	45.2 HP (33.9 KW)
▶ Rear PTO Speeds(1st)	540 rpm
▶ Rear PTO Speeds(2nd)	1,000 rpm
▶ Mid PTO Speeds	N/A
▶ Front PTO Speeds	Same as Engine Speed
Brakes and Clutch	
▶ Brakes	Wet Disc

▶Clutch	Dry Single Plate
<b>Dimensions w/ AG Tire</b>	
▶Length w/ 3-point hitch	130.5 in. (3,316 mm)
▶Width	69.3 in. (1,760 mm)
▶Height from Top of ROPS	99.6 in. (2,530)
▶From Top of the Highest Point	
▶Wheelbase	75.6 in. (1,920 mm)
▶Ground Clearance	17.5 in. (445 mm)
▶Front Tread Ag Tires - Min	57.5 in. (1,461 mm)
▶Front Tread Ag Tires - Max	
▶Rear Tread Ag Tires - Min	53.9 in. (1,370 mm)
▶Rear Tread Ag Tires - Max	61.6 in. (1,564 mm)
▶Turning Radius w/ Brake	9.6 ft. (2.92 m)
▶Turning Radius w/o Brake	11.7 ft. (3.56 m)
<b>Hydraulics</b>	
▶Total Pump Flow	14.2 gpm (53.8 Lpm)
▶Main Pump Capacity	9.9 gpm (37.4 Lpm)
▶Power Steering Pump Capacity	4.3 gpm (16.4 Lpm)
<b>3-Point Hitch</b>	
▶Standard Category (Optional Category)	Cat. 2 (1)
▶Lift Capacity, 24" aft of hitch, lb(kg)	2,866 lbs. (1,300 kg)
▶Control Type	Position, Draft and Mixed
<b>Weight</b>	
▶Weight w/ Ag Tires w/ ROPS	4,795 lbs. (2,175kg)

### ›Equipment & Panel

Standard Equipment	Optional Equipment	Instrument Panel
Foldable ROPS	Sunshade	Tachometer with Hour Meter
Hydrostatic Power Steering	Front PTO	Tachometer Gauge
Rear Differential Lock	Front suitcase weights	Fuel Gauge
Wet Disc Brakes		Temperature Gauge
Hand & Foot Throttles		Oil Pressure Indicator
Swing Drawbar		PTO Indicator
Adjustable Seat with Seat belt		Low Fuel Indicator
Headlights		Hydraulic Warning
Safety Lights		Glow Plug Indicator
Safety Start Switch		Separate Detector
Rear Working Light		Low Coolant Indicator
Dual Remote Hydraulic Valve		
Pre Cleaner (Cab only)		
Flip up PTO Guard		
Foot-operated Tilt Steering Wheel		
Full Open Hood		
Telescopic Lower Link Ends		
Telescopic stabilizer		
Crank type lift rod		
Bevel gear front wheel drive		
4WD indicator		
Single lever joystick		
Side mount hydraulic couplers		
Tool Box		
Cup holder		
Trailer electrical outlet		

### ›Tires

 Ag	▶Ag1 4WD Front	9.5x20/6
	▶Ag1 4WD Rear	14.9x28
	▶Ag2 4WD Front	N/A
	▶Ag2 4WD Rear	N/A
 Turf	▶Turf1 4WD Front	29x12.5x15/4
	▶Turf1 4WD Rear	44x18-20
	▶Turf2 4WD Front	N/A
	▶Turf2 4WD Rear	N/A
 Ind	▶Ind1 4WD Front	14x17.5
	▶Ind1 4WD Rear	18.4x24/8
	▶Ind2 4WD Front	N/A
	▶Ind2 4WD Rear	N/A

›Attachments

<a href="#">Front End Loaders</a>	▶KL551 ,
<a href="#">Backhoes</a>	▶KB2485 ,

›Implements

<a href="#">Mowers</a>	▶KMR03-84 ,
<a href="#">Tillers</a>	▶KT03-65 , KT03-73 ,