

DK75C

Specifications



Engine	
▶ Engine Model	1104D4-44T
▶ Engine Gross Power	74.4 HP (55.5 KW)
▶ Rated Speed	2,200 rpm
▶ No. of Cylinder	4
▶ Fuel Type	Diesel
▶ Aspiration	Turbocharged
▶ Displacement	268.5 cu.in. (4,400 cc)
▶ Fuel Tank Capacity	33 gal (125 L)
▶ Pre-heating System	Intake Heater
Transmission	
▶ Transmission Type	Manual
▶ Shuttle	Fully Synchronized
▶ Main Gear	Synchronized
▶ No. of Travel Speed Forward / Reverse	12F/12R
▶ Min. Travel Speed of Forward w/ Ag1 @ Engine rated speed	1.09 mph (1.76 kph)
▶ Max. Travel Speed of Forward w/ Ag1 @ Engine rated speed	19.37 mph (31.18 kph)
Power Take-Off	
▶ PTO Type Trans	Independent
▶ PTO Power	58.4 HP (43.5 KW)
▶ Rear PTO Speeds(1st)	540 rpm
▶ Rear PTO Speeds(2nd)	N/A
▶ Mid PTO Speeds	N/A
▶ Front PTO Speeds	N/A
Brakes and Clutch	
▶ Brakes	Hydraulic Wet Disc

▶Clutch	Dry Single Plate
Dimensions w/ AG Tire	
▶Length w/ 3-point hitch	162.2 in. (4,120 mm)
▶Width	77.8 in. (1,977 mm)
▶Height from Top of ROPS	N/A
▶Height from Top of ROPS Cab	108.3 in. (2,750 mm)
▶Height from Top of ROPS Folded	N/A
▶From Top of the Highest Point	108.3 in. (2,750 mm)
▶Wheelbase	90.7 in. (2,305 mm)
▶Ground Clearance	16.7 in. (425 mm)
▶Front Tread Ag Tires - Min	59.7 in. (1,516 mm)
▶Front Tread Ag Tires - Max	67.6 in. (1,716 mm)
▶Rear Tread Ag Tires - Min	61.6 in. (1,565 mm)
▶Rear Tread Ag Tires - Max	77.5 in. (1,968 mm)
▶Turning Radius w/ Brake	12.8 ft. (3.9 m)
▶Turning Radius w/o Brake	
Hydraulics	
▶Total Pump Flow	22.1 gpm (83.6 Lpm)
▶Main Pump Capacity	12.8 gpm (48.4 Lpm)
▶Power Steering Pump Capacity	9.3 gpm (35.2 Lpm)
3-Point Hitch	
▶Standard Category (Optional Category)	Cat. 2 (1)
▶Lift Capacity, 24" aft of hitch, lb(kg)	5,290 lbs. (2,400 kg)
▶Control Type	Position, Draft and Mixed
Weight	
▶Weight w/ Ag Tires w/ ROPS	N/A
▶Weight w/ Ag Tires w/ Cab	7,749 lbs. (3,515 kg)

›Equipment & Panel

Standard Equipment	Optional Equipment	Instrument Panel
Telescopic 3 Point Hitch Ends	2nd & 3rd Remote Hydraulic Valve	Tachometer with Hour Meter
Telescopic Stabilizers	Front Weights	Temperature Gauge
Crank Adjustable Lift Link	Rear Sub Cylinder	Fuel Gauge
Side Mount Hydraulic Couplers	Cooler	PTO on Indicator
Single Lever Joy Stick for Loader Operation	Rear Wiper	Oil Pressure Indicator
Hydrostatic Power Steering	AM/FM Radio CD Player	Low Fuel Indicator
Rear Differential Lock		Battery Charge Lamp
Hydraulic Brakes		Glow Plug Indicator
Hand & Foot Throttles		4WD Indicator
Adjustable Drawbar		
Adjustable Seat with seatbelts		
Head Lights / Safety Lights		
Safety Start Switch		
Front & Rear Working Light		
Single Remote Hydraulic Valve		
Single Element Air Cleaner		
Tilt Steering Wheel		
Oil Cooler		
4WD Push button engage		
Flip up PTO guard		
Power outlet (3P) & 7 Pole Socket		
Front Wiper		

›Tires

 Ag	›Ag1 4WD Front	11.2x24/8, tubeless
	›Ag1 4WD Rear	16.9x30/8, bias tube
	›Ag2 4WD Front	N/A
	›Ag2 4WD Rear	N/A
 Turf	›Turf1 4WD Front	N/A
	›Turf1 4WD Rear	N/A
	›Turf2 4WD Front	N/A
	›Turf2 4WD Rear	N/A
 Ind	›Ind1 4WD Front	N/A
	›Ind1 4WD Rear	N/A
	›Ind2 4WD Front	N/A
	›Ind2 4WD Rear	N/A

>Attachments

[Front End Loaders](#)

▶KL901 ,