

DK90C

Specifications



Engine	
▶ Engine Model	1104D4-44T
▶ Engine Gross Power	91.2 HP (68 KW)
▶ Rated Speed	2,200 rpm
▶ No. of Cylinder	4
▶ Fuel Type	Diesel
▶ Aspiration	Turbocharged
▶ Displacement	268.5 cu.in. (4,400 cc)
▶ Fuel Tank Capacity	33 gal (125 L)
▶ Pre-heating System	Glow plugs
Transmission	
▶ Transmission Type	Manual
▶ Shuttle	Synchronized
▶ Main Gear	Synchronized
▶ No. of Travel Speed Forward / Reverse	16F/16R
▶ Min. Travel Speed of Forward w/ Ag1 @ Engine rated speed	0.16 mph (0.25 kph)
▶ Max. Travel Speed of Forward w/ Ag1 @ Engine rated speed	21.57 mph (34.72 kph)
Power Take-Off	
▶ PTO Type Trans	Independent/ Ground
▶ PTO Power	78 HP (57 KW)
▶ Rear PTO Speeds(1st)	540 rpm
▶ Rear PTO Speeds(2nd)	1,000 rpm
▶ Mid PTO Speeds	N/A
▶ Front PTO Speeds	N/A
Brakes and Clutch	
▶ Brakes	Wet Disc Type (Hydraulic)

▶Clutch	Dry Single Plate ceramic
Dimensions w/ AG Tire	
▶Length w/ 3-point hitch	162.2 in. (4,120 mm)
▶Width	78.7 in. (2,000 mm)
▶Height from Top of ROPS	N/A
▶Height from Top of ROPS Cab	111.0 in. (2,820 mm)
▶Height from Top of ROPS Folded	N/A
▶From Top of the Highest Point	111.0 in. (2,820 mm)
▶Wheelbase	90.7 in. (2,305 mm)
▶Ground Clearance	19.5 in. (495 mm)
▶Front Tread Ag Tires - Min	59.70 in. (1,516 mm)
▶Front Tread Ag Tires - Max	67.6 in. (1,716 mm)
▶Rear Tread Ag Tires - Min	61.6 in. (1,565 mm)
▶Rear Tread Ag Tires - Max	77.5 in. (1,968 mm)
▶Turning Radius w/ Brake	12.8 ft. (3.9 m)
▶Turning Radius w/o Brake	
Hydraulics	
▶Total Pump Flow	22.1 gpm (83.6 Lpm)
▶Main Pump Capacity	12.8 gpm (48.4 Lpm)
▶Power Steering Pump Capacity	9.3 gpm (35.2 Lpm)
3-Point Hitch	
▶Standard Category (Optional Category)	Cat. 2 (1)
▶Lift Capacity, 24" aft of hitch, lb(kg)	5,290 lbs. (2,400 kg)
▶Control Type	Position, Draft, Mixed Control
Weight	
▶Weight w/ Ag Tires w/ ROPS	N/A
▶Weight w/ Ag Tires w/ Cab	8,905 lbs. (4,039 kg)

›Equipment & Panel

Standard Equipment	Optional Equipment	Instrument Panel
Telescopic 3 Point Hitch Ends Telescopic Stabilizers Crank Adjustable Lift Link Creep Speed Gear Side Mount Hydraulic Couplers Single Lever Joy Stick For Loader Operation Hydrostatic Power Steering Rear Differential Lock Hydraulic Brakes Hand & Foot Throttles Adjustable Drawbar Adjustable Seat Head Lights / Safety Lights Safety Start Switch Front & Rear Working Light Dual Remote Hydraulic Valves Single Element Air Cleaner Ground PTO Tilt Steering Wheel Oil Cooler 4WD, Push Button Engaged Flip-up PTO Guard AM/FM Radio CD Player (w/ connection for MP3) Rear Defogger Power Outlet (3P) and 7 Pole Socket Front and Rear Wiper	3rd Remote Hydraulic Valve(Detent Floating Valve) Rear Sub Cylinder Front End Weights Food & Beverage Cooler/Warmer	Tachometer with Hour Meter Temperature Gauge Fuel Gauge PTO on Indicator Oil Pressure Indicator Low Fuel Indicator Battery Charge Lamp Glow Plug Indicator 4WD Indicator

>Tires

 Ag	▶Ag1 4WD Front	12.4X24/8, tubeless
	▶Ag1 4WD Rear	18.4X34/8, bias tube
	▶Ag2 4WD Front	N/A
	▶Ag2 4WD Rear	N/A
 Turf	▶Turf1 4WD Front	N/A
	▶Turf1 4WD Rear	N/A
	▶Turf2 4WD Front	N/A
	▶Turf2 4WD Rear	N/A
 Ind	▶Ind1 4WD Front	N/A
	▶Ind1 4WD Rear	N/A
	▶Ind2 4WD Front	N/A
	▶Ind2 4WD Rear	N/A

>Attachments

Front End Loaders	▶KL901 ,
-----------------------------------	----------