

LK30 (TLB)

Specifications






Engine	
▶ Engine Model	3A150LXB
▶ Engine Gross Power	30 HP (22.4 KW)
▶ Rated Speed	2,600 rpm
▶ No. of Cylinder	3
▶ Fuel Type	Diesel
▶ Aspiration	Natural
▶ Displacement	91.5 cu.in. (1,500 cc)
▶ Fuel Tank Capacity	7.4 gal (28 L)
▶ Pre-heating System	Glow plugs
Transmission	
▶ Transmission Type	Manual
▶ Shuttle	Constant
▶ Main Gear	Synchronized
▶ No. of Travel Speed Forward / Reverse	8F/8R
▶ Min. Travel Speed of Forward w/ Ag1 @ Engine rated speed	0.83 mph (1.34 kph)
▶ Max. Travel Speed of Forward w/ Ag1 @ Engine rated speed	11.95 mph (19.23 kph)
Power Take-Off	
▶ PTO Type Trans	Live, Dependent
▶ PTO Power	23 HP (17.2 KW)
▶ Rear PTO Speeds(1st)	540 rpm @ 2610 Engine rpm
▶ Rear PTO Speeds(2nd)	1,000 rpm @ 2626 Engine rpm
▶ Mid PTO Speeds	N/A
▶ Front PTO Speeds	Same as Engine Speed
Brakes and Clutch	
▶ Brakes	Wet Disc

▶Clutch	Dry Dual Plate
Dimensions w/ AG Tire	
▶Length w/ 3-point hitch	111.4 in. (2,830 mm)
▶Width	51.7 in. (1,314 mm)
▶Height from Top of ROPS	88.6 in. (2,250 mm)
▶Height from Top of ROPS Cab	N/A
▶Height from Top of ROPS Folded	
▶From Top of the Highest Point	
▶Wheelbase	64.6 in. (1,640 mm)
▶Ground Clearance	10.8 in. (275 mm)
▶Front Tread Ag Tires - Min	43.5 in. (1,105 mm)
▶Front Tread Ag Tires - Max	
▶Rear Tread Ag Tires - Min	40.2 in. (1020 mm)
▶Rear Tread Ag Tires - Max	49.9 in. (1,268 mm)
▶Turning Radius w/ Brake	9.18 ft. (2.8 m)
▶Turning Radius w/o Brake	
Hydraulics	
▶Total Pump Flow	12.7 gpm (48.3 Lpm)
▶Main Pump Capacity	
▶Power Steering Pump Capacity	
3-Point Hitch	
▶Standard Category (Optional Category)	Cat. 1 (N/A)
▶Lift Capacity, 24" aft of hitch, lb(kg)	1,764 lbs. (800 kg)
▶Control Type	Position
Weight	
▶Weight w/ Ag Tires w/ ROPS	2,897 lbs. (1,314 kg)
▶Weight w/ Ag Tires w/ Cab	N/A

›Equipment & Panel

Standard Equipment	Optional Equipment	Instrument Panel
Foldable ROPS Hydrostatic Power Steering Differential Lock Rear PTO Wet Disc Brakes Hydraulic Pump with Diverting Block Hand & Foot Throttles Adjustable Drawbar Adjustable Seat with Seat belt Headlights Safety Lights Safety Start Switch	Front Weights Remote Valve Sunshade with 4-Post ROPS with TLB package Adjustable, Flip-over Seat with TLB package	Tachometer with Hour Meter Temperature Gauge Fuel Gauge Oil Pressure Indicator Low Fuel Indicator Glow Plug Indicator Low Coolant Indicator

›Tires

 Ag	›Ag1 4WD Front	7-14/6
	›Ag1 4WD Rear	11.2-24/6
	›Ag2 4WD Front	N/A
	›Ag2 4WD Rear	N/A
 Turf	›Turf1 4WD Front	27x8.5-15/4
	›Turf1 4WD Rear	41x14-20/4
	›Turf2 4WD Front	N/A
	›Turf2 4WD Rear	N/A
 Ind	›Ind1 4WD Front	25x8.5-14/6
	›Ind1 4WD Rear	15-19.5/6
	›Ind2 4WD Front	N/A
	›Ind2 4WD Rear	N/A

›Attachments

<u>Front End Loaders</u>	›KL1231 ,
<u>Backhoes</u>	›KB2376 ,

›Implements

<u>Mowers</u>	›KMR03-60 , KMR03-72 ,
<u>Tillers</u>	›KT03-47 , KT03-55 , KT03-59 ,