

- [Products](#)
- [Support](#)
- [About TYM](#)
- [Contacts](#)
- [Customer Review](#)
- [Team TYM Dealers](#)



- [» Features](#)
- [» Specification](#)
- [» Attachments](#)
- [» Gallery](#)

Tractor Quick Select

| | |
|--------------------------|-------------------------|
| Manufacturer | Mitsubishi |
| Model | S3L |
| HP(kw)-Gross | 23(16.9) |
| HP(kw) | 17.4(15.9) |
| Engine speed | 2700 |
| No. of cylinders | 3 |
| Displacement-cu.in. (cc) | 68.7(1125) |
| Ignition | Dual Dry |
| Battery | 12V.50A |
| Injection System Type | Indirect Fuel Injection |



| Powertrain | T233HST |
|--------------------|--------------------|
| Transmission type | HST |
| No. of Speeds | Infinite / 2 Range |
| Forward speed, mph | 10.5(17) |
| Clutch | Wet Disc |
| Drivetrain | Hydrostatic |
| Final Drive | N/A |

| Hydraulic system | T233HST |
|---|----------------|
| Pump type | Dual Gear Pump |
| Implement pump cap.gpm(L/Min) | 5.0 (18.9) |
| Steering pump cap. gpm (L/Min) | 2.6 (10) |
| Max Total flow gpm (L/Min) | 7.6(28.9) |
| Category, 3 Point Hitch | 1 |
| Hitch lift capacity, lb. (kg) | 1534(700) |
| Lift capacity at 24 inches behind link ends, lb(kg) | 1102(500) |
| Lift Control type | Position |
| Joy Stick Valve | Standard |
| No. of standard remote valves-option | 1 |

| PTO | T233 |
|-----------------------------|-------------|
| PTO Type | Independent |
| PTO Control | Electric |
| PTO Mid (rpm)-Option | 2000 |
| PTO Rear (rpm) | 540 |
| PTO Shaft Diameter in. (mm) | 1 3/8 (32) |

| Capacities | T233HST |
|---|----------|
| Capacity, U.S. gal. (L) | 6.6 (25) |
| Hydraulic System U.S. qt. (L) | 9.3(8.8) |
| Hydraulic Capacity (with filter) U.S. qt. (L) | 6.0(5.7) |
| Hydr. System, U.S. gal. (L) | 9.5(36) |
| Hydraulic Tank Capacity qt. (L) | 8.6(8.2) |

| Dimensions | |
|---------------------------------------|--------------|
| Overall length, in. (mm) | 134.2 (3400) |
| Overall width, in. (mm) | 52.8(1342) |
| Wheelbase, in. (mm) | 58.3(1480) |
| Height to top of ROPS, in. (mm) | 97.2(2470) |
| Min. Ground Clearance, in. (mm) | 7.71(196) |
| Min. Turn Radius, in (mm) with Brakes | 98.5(2502) |
| Min. Turn Radius, in (mm) w/o brakes | 105.5 (2682) |



| | |
|-------------------------------|------|
| Agricultural Rear | - |
| Industrial Front | 23x8 |
| Industrial Rear | 12x7 |
| Roll Over Protection Standard | ROP |
| Total Weight, lb (kg) | 2028 |

| T233/T273/T293 Cabin | Cab |
|----------------------|--------------|
| Height, in. (mm) | 66.9 (1,700) |
| Width, in. (mm) | 44.5 (1,130) |
| Depth, in. (mm) | 54.7 (1,390) |
| Weight, lbs (kg) | 220.5 (100) |
| Lamps Front | 2 |
| Lamps Rear | 1 |
| Interior Temp | Standard |
| Window Wiper | Standard |
| Windows | 2 |
| Steering | Standard |
| Window (Open/Close) | Standard |
| Front Air Vent | 2 Outlets |

TYM TRACTORS



[HOME](#) | [CONTACT](#) | [FIND A DEALER](#)



Follow us: